

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: RSA

Report Number: P219830

Luminaire Tested: **MRZ-1-REC-X-2-L30-80-WFL-UNV-X-STD**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P219830  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14880)  
Test Lab: INNOVATION CENTER (G1)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: RSA  
Catalog Number: MRZ-1-REC-X-2-L30-80-WFL-UNV-X-STD  
Description: MRZ INTEGRAL LED DOWNLIGHT  
55 DEGREE WIDE FLOOD OPTIC, LIGHT LEVEL2  
Light Source: (1) 3000K CCT, 80 CRI LEDS  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 851.3 lumens  
Efficiency: N/A  
Efficacy: 96.7 lumens/watt  
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.91  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 8.8  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P219830

CATALOG NUMBER: MRZ-1-REC-X-2-L30-80-WFL-UNV-X-STD

### Luminous Intensity Polar Plot





TEST NUMBER: P219830

CATALOG NUMBER: MRZ-1-REC-X-2-L30-80-WFL-UNV-X-STD

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	108	105	111	108	106	103	104	102	100	100	99	97	97	96	94	93
2	107	102	97	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85
3	101	94	89	85	99	93	88	84	90	86	83	88	84	81	85	82	80	78
4	95	87	81	77	94	86	81	76	84	79	76	82	78	75	80	77	74	72
5	90	81	75	70	88	80	74	70	78	73	69	77	72	69	75	71	68	67
6	85	76	69	65	84	75	69	65	73	68	64	72	67	64	71	66	63	62
7	81	71	64	60	79	70	64	60	69	63	59	68	63	59	66	62	59	57
8	76	66	60	56	75	66	60	56	65	59	55	64	59	55	63	58	55	53
9	73	62	56	52	71	62	56	52	61	55	52	60	55	51	59	55	51	50
10	69	59	53	49	68	58	52	48	57	52	48	57	52	48	56	51	48	47

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	421593
5°	423699
10°	411915
15°	376857
20°	337025
25°	302950
30°	249360
35°	177620
40°	117477
45°	74868
50°	46361
55°	28644
60°	16479
65°	8522
70°	4472
75°	4003
80°	0
85°	0



TEST NUMBER: P219830

CATALOG NUMBER: MRZ-1-REC-X-2-L30-80-WFL-UNV-X-STD

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	80.6	9.5
10°-20°	205.7	24.2
20°-30°	252.0	29.6
30°-40°	185.9	21.8
40°-50°	86.0	10.1
50°-60°	31.2	3.7
60°-70°	8.1	0.9
70°-80°	1.8	0.2
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	538.4	63.2
0°-40°	724.3	85.1
0°-60°	841.5	98.8
0°-90°	851.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	851.3	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	854	
5°	856	81
15°	738	206
25°	556	252
35°	295	186
45°	107	86
55°	33	31
65°	7	8
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P219830

CATALOG NUMBER: MRZ-1-REC-X-2-L30-80-WFL-UNV-X-STD

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	854.5
2.5°	853.4
5°	855.5
7.5°	846.1
10°	822.2
12.5°	785.7
15°	737.8
17.5°	685.7
20°	641.9
22.5°	603.3
25°	556.5
27.5°	502.3
30°	437.7
32.5°	365.8
35°	294.9
37.5°	233.4
40°	182.4
42.5°	140.7
45°	107.3
47.5°	81.3
50°	60.4
52.5°	44.8
55°	33.3
57.5°	24.0
60°	16.7
62.5°	11.5
65°	7.3
67.5°	4.2
70°	3.1
72.5°	2.1
75°	2.1
77.5°	1.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)