

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: RSA

Report Number: P219583

Luminaire Tested: **MRZ-1-REC-X-2-L35-80-NFL-UNV-X-STD-HEX**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P219583
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14871)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: RSA
Catalog Number: MRZ-1-REC-X-2-L35-80-NFL-UNV-X-STD-HEX
Description: MRZ INTEGRAL LED DOWNLIGHT
25 DEGREE NARROW FLOOD OPTIC WITH HEX LOUVER, LIGHT LEVEL2
Light Source: (1) 3500K CCT, 80 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 665.3 lumens
Efficiency: N/A
Efficacy: 75.6 lumens/watt
Spacing Criteria (0/90/45): 0.36 / 0.36 / 0.35
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 8.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P219583

CATALOG NUMBER: MRZ-1-REC-X-2-L35-80-NFL-UNV-X-STD-HEX

Luminous Intensity Polar Plot





TEST NUMBER: P219583

CATALOG NUMBER: MRZ-1-REC-X-2-L35-80-NFL-UNV-X-STD-HEX

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20							
RC	80				70				50				30				10							
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10				
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	111	106	106	106	106	102	102	102	102	100	100	100	100
1	115	113	112	110	113	111	110	108	107	106	105	105	104	103	102	102	100	100	99	99	97	97	97	97
2	112	109	106	104	110	107	105	103	104	102	100	100	101	100	98	98	99	97	96	96	95	95	95	95
3	109	105	101	99	107	103	100	98	101	99	97	97	99	97	95	95	97	95	94	94	92	92	92	92
4	106	101	98	95	105	100	97	94	98	95	93	93	96	94	92	92	95	93	91	91	90	90	90	90
5	103	98	94	92	102	97	94	91	96	93	91	91	94	92	90	90	93	91	89	89	88	88	88	88
6	101	95	92	89	100	95	91	89	93	90	88	88	92	90	88	88	91	89	87	87	86	86	86	86
7	99	93	89	87	98	92	89	86	91	88	86	86	90	88	86	86	89	87	85	85	84	84	84	84
8	96	91	87	84	95	90	87	84	89	86	84	84	88	86	84	84	88	85	83	83	82	82	82	82
9	94	88	85	82	94	88	85	82	87	84	82	82	87	84	82	82	86	83	82	82	81	81	81	81
10	92	86	83	81	92	86	83	81	86	82	80	80	85	82	80	80	84	82	80	80	79	79	79	79

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2191839
5°	1847732
10°	1207187
15°	425790
20°	137246
25°	71151
30°	33157
35°	15238
40°	7085
45°	3838
50°	1689
55°	946
60°	1085
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P219583

CATALOG NUMBER: MRZ-1-REC-X-2-L35-80-NFL-UNV-X-STD-HEX

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	313.8	47.2
10°-20°	265.5	39.9
20°-30°	62.4	9.4
30°-40°	17.5	2.6
40°-50°	4.4	0.7
50°-60°	1.3	0.2
60°-70°	0.4	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	641.7	96.5
0°-40°	659.2	99.1
0°-60°	664.9	99.9
0°-90°	665.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	665.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4442	
5°	3731	314
15°	834	266
25°	131	62
35°	25	17
45°	6	4
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P219583

CATALOG NUMBER: MRZ-1-REC-X-2-L35-80-NFL-UNV-X-STD-HEX

CANDELA DISTRIBUTION (FULL):

0°	
0°	4442.5
2.5°	4237.2
5°	3730.8
7.5°	3089.5
10°	2409.6
12.5°	1601.3
15°	833.6
17.5°	430.5
20°	261.4
22.5°	181.2
25°	130.7
27.5°	90.1
30°	58.2
32.5°	38.4
35°	25.3
37.5°	16.5
40°	11.0
42.5°	7.7
45°	5.5
47.5°	3.3
50°	2.2
52.5°	2.2
55°	1.1
57.5°	1.1
60°	1.1
62.5°	1.1
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)