

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: SHAPER

Report Number: P701880

Luminaire Tested: 340-4C-10-D010 / 340-EU4C-1020-9035-4LBW1LI-CC

Issue Date: 8/30/2023

Test Information

Test Method: LM-79-2019
Report Number: P701880
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-3)
Test Lab: INNOVATION CENTER
Issue Date: 8/30/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: SHAPER
Catalog Number: 340-4C-10-D010 / 340-EU4C-1020-9035-4LBW1LI-CC
Description: FARALLON 4" LED GLASS DOWNLIGHT. CYLINDRICAL CLEAR GLASS KIT.
Light Source: 3500K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 716.4 lumens
Efficiency: N/A
Efficacy: 73.1 lumens/watt
Spacing Criteria (0/90/45): 0.4 / 0.4 / 0.64
Luminous Opening: Circular (Dia: 0.34' x H: 0')
CIE Type: Direct

Input Watts (W): 9.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P701880

CATALOG NUMBER: 340-4C-10-D010 / 340-EU4C-1020-9035-4LBW1LI-CC

Luminous Intensity Polar Plot



TEST NUMBER: P701880

CATALOG NUMBER: 340-4C-10-D010 / 340-EU4C-1020-9035-4LBW1LI-CC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	108	105	111	108	106	103	104	102	100		100	99	97		97	96	94	93
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91	89	87	85
3	101	95	89	85	99	93	88	85	91	87	83		88	85	82		86	83	81	79
4	96	88	82	78	94	87	82	78	85	80	77		83	79	76		81	78	75	73
5	91	82	76	72	89	82	76	72	80	75	71		78	74	70		76	73	70	68
6	87	77	71	67	85	77	71	67	75	70	66		74	69	66		72	68	65	64
7	82	73	67	62	81	72	66	62	71	66	62		70	65	61		68	64	61	60
8	78	69	63	58	77	68	62	58	67	62	58		66	61	58		65	61	57	56
9	75	65	59	55	74	64	59	55	63	58	55		63	58	54		62	57	54	53
10	71	62	56	52	70	61	55	52	60	55	52		59	55	51		59	54	51	50

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	166181
5°	132738
10°	94877
15°	80438
20°	68946
25°	58356
30°	38356
35°	27369
40°	20909
45°	12302
50°	8120
55°	5905
60°	3851
65°	3458
70°	2950
75°	2106
80°	1603
85°	1065

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 12302 cd/sqm

TEST NUMBER: P701880

CATALOG NUMBER: 340-4C-10-D010 / 340-EU4C-1020-9035-4LBW1LI-CC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	96.9	13.5
10°-20°	186.3	26.0
20°-30°	201.2	28.1
30°-40°	124.3	17.3
40°-50°	62.3	8.7
50°-60°	26.1	3.6
60°-70°	12.3	1.7
70°-80°	5.4	0.8
80°-90°	1.2	0.2
90°-100°	0.1	0.0
100°-110°	0.3	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	484.4	67.6
0°-40°	608.7	85.0
0°-60°	697.1	97.3
0°-90°	716.0	99.9
90°-120°	0.4	0.1
90°-150°	0.4	0.1
90°-180°	0.0	0.0
0°-180°	716.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1433	
5°	1140	97
15°	670	186
25°	456	201
35°	193	124
45°	75	62
55°	29	26
65°	13	12
75°	5	5
85°	1	1
90°	0	0
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0

TEST NUMBER: P701880

CATALOG NUMBER: 340-4C-10-D010 / 340-EU4C-1020-9035-4LBW1LI-CC

CANDELA DISTRIBUTION (FULL):

0°	
0°	1432.8
1°	1425.7
2°	1385.5
3°	1319.2
4°	1233.2
5°	1140.1
6°	1047.0
7°	962.6
8°	895.5
9°	845.0
10°	805.6
11°	771.6
12°	742.5
13°	717.2
14°	694.3
15°	669.9
16°	645.4
17°	617.8
18°	592.5
19°	572.0
20°	558.6
21°	547.6
22°	533.4
23°	513.6
24°	486.8
25°	456.0
27.5°	366.9
30°	286.4
32.5°	231.2
35°	193.3
37.5°	165.7
40°	138.1
42.5°	103.4
45°	75.0
47.5°	56.8
50°	45.0
52.5°	37.1
55°	29.2
57.5°	20.5
60°	16.6
62.5°	14.2
65°	12.6
67.5°	10.3
70°	8.7
72.5°	6.3

TEST NUMBER: P701880

CATALOG NUMBER: 340-4C-10-D010 / 340-EU4C-1020-9035-4LBW1LI-CC

CANDELA DISTRIBUTION (continued):

	0°
75°	4.7
77.5°	3.9
80°	2.4
82.5°	1.6
85°	0.8
87.5°	0.8
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.8
102.5°	0.8
105°	0.0
107.5°	0.0
110°	0.0
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)