

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: SHAPER

Report Number: P701915

Luminaire Tested: 340-4C-15-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

Issue Date: 8/30/2023

Test Information

Test Method: LM-79-2019
Report Number: P701915
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-3)
Test Lab: INNOVATION CENTER
Issue Date: 8/30/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: SHAPER
Catalog Number: 340-4C-15-D010 / 340-EU4C-1020-9024-4LBW1LI-CC
Description: FARALLON 4" LED GLASS DOWNLIGHT. CYLINDRICAL CLEAR GLASS KIT.
Light Source: 2400K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 915.7 lumens
Efficiency: N/A
Efficacy: 58.0 lumens/watt
Spacing Criteria (0/90/45): 0.4 / 0.4 / 0.64
Luminous Opening: Circular (Dia: 0.34' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P701915

CATALOG NUMBER: 340-4C-15-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

Luminous Intensity Polar Plot



TEST NUMBER: P701915

CATALOG NUMBER: 340-4C-15-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	108	105	111	108	106	103	104	102	100		100	99	97		97	96	94	93
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91	89	87	85
3	101	95	89	85	99	93	88	85	91	87	83		88	85	82		86	83	81	79
4	96	88	82	78	94	87	82	78	85	80	77		83	79	76		81	78	75	73
5	91	82	76	72	89	82	76	72	80	75	71		78	74	70		76	73	70	68
6	87	77	71	67	85	77	71	67	75	70	66		74	69	66		72	68	65	64
7	82	73	67	62	81	72	66	62	71	66	62		70	65	61		68	64	61	60
8	78	69	63	58	77	68	62	58	67	62	58		66	61	58		65	61	57	56
9	75	65	59	55	74	64	59	55	63	58	55		63	58	54		62	57	54	53
10	71	62	56	52	70	61	55	52	60	55	52		59	55	51		59	54	51	50

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	212435
5°	169680
10°	121282
15°	102820
20°	88139
25°	74608
30°	49030
35°	34987
40°	26723
45°	15714
50°	10375
55°	7542
60°	4918
65°	4418
70°	3764
75°	2734
80°	2004
85°	1331

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 15714 cd/sqm

TEST NUMBER: P701915

CATALOG NUMBER: 340-4C-15-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	123.9	13.5
10°-20°	238.1	26.0
20°-30°	257.2	28.1
30°-40°	158.9	17.3
40°-50°	79.6	8.7
50°-60°	33.4	3.6
60°-70°	15.7	1.7
70°-80°	6.9	0.8
80°-90°	1.5	0.2
90°-100°	0.1	0.0
100°-110°	0.4	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	619.2	67.6
0°-40°	778.1	85.0
0°-60°	891.1	97.3
0°-90°	915.2	99.9
90°-120°	0.5	0.1
90°-150°	0.5	0.1
90°-180°	1.0	0.1
0°-180°	915.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1832	
5°	1457	124
15°	856	238
25°	583	257
35°	247	159
45°	96	80
55°	37	33
65°	16	16
75°	6	7
85°	1	1
90°	0	0
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0

TEST NUMBER: P701915

CATALOG NUMBER: 340-4C-15-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

CANDELA DISTRIBUTION (FULL):

0°	
0°	1831.6
1°	1822.5
2°	1771.1
3°	1686.4
4°	1576.4
5°	1457.4
6°	1338.4
7°	1230.5
8°	1144.8
9°	1080.2
10°	1029.8
11°	986.4
12°	949.1
13°	916.8
14°	887.6
15°	856.3
16°	825.0
17°	789.7
18°	757.5
19°	731.2
20°	714.1
21°	700.0
22°	681.8
23°	656.6
24°	622.3
25°	583.0
27.5°	469.0
30°	366.1
32.5°	295.5
35°	247.1
37.5°	211.8
40°	176.5
42.5°	132.1
45°	95.8
47.5°	72.6
50°	57.5
52.5°	47.4
55°	37.3
57.5°	26.2
60°	21.2
62.5°	18.2
65°	16.1
67.5°	13.1
70°	11.1
72.5°	8.1

TEST NUMBER: P701915

CATALOG NUMBER: 340-4C-15-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

CANDELA DISTRIBUTION (continued):

	0°
75°	6.1
77.5°	5.0
80°	3.0
82.5°	2.0
85°	1.0
87.5°	1.0
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	1.0
102.5°	1.0
105°	0.0
107.5°	0.0
110°	0.0
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)