

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: SHAPER

Report Number: P701985

Luminaire Tested: 340-4C-20-D010 / 340-EU4C-1020-9030-4LBW1LI-CC

Issue Date: 8/30/2023

Test Information

Test Method: LM-79-2019
Report Number: P701985
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-3)
Test Lab: INNOVATION CENTER
Issue Date: 8/30/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: SHAPER
Catalog Number: 340-4C-20-D010 / 340-EU4C-1020-9030-4LBW1LI-CC
Description: FARALLON 4" LED GLASS DOWNLIGHT. CYLINDRICAL CLEAR GLASS KIT.
Light Source: 3000K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1396.6 lumens
Efficiency: N/A
Efficacy: 64.1 lumens/watt
Spacing Criteria (0/90/45): 0.4 / 0.4 / 0.64
Luminous Opening: Circular (Dia: 0.34' x H: 0')
CIE Type: Direct

Input Watts (W): 21.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P701985

CATALOG NUMBER: 340-4C-20-D010 / 340-EU4C-1020-9030-4LBW1LI-CC

Luminous Intensity Polar Plot



TEST NUMBER: P701985

CATALOG NUMBER: 340-4C-20-D010 / 340-EU4C-1020-9030-4LBW1LI-CC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	108	105	111	108	106	103	104	102	100		100	99	97		97	96	94	93
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91	89	87	85
3	101	95	89	85	99	93	88	85	91	87	83		88	85	82		86	83	81	79
4	96	88	82	78	94	87	82	78	85	80	77		83	79	76		81	78	75	73
5	91	82	76	72	89	82	76	72	80	75	71		78	74	70		76	73	70	68
6	87	77	71	67	85	77	71	67	75	70	66		74	69	66		72	68	65	64
7	82	73	67	62	81	72	66	62	71	66	62		70	65	61		68	64	61	60
8	78	69	63	58	77	68	62	58	67	62	58		66	61	58		65	61	57	56
9	75	65	59	55	74	64	59	55	63	58	55		63	58	54		62	57	54	53
10	71	62	56	52	70	61	55	52	60	55	52		59	55	51		59	54	51	50

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	323999
5°	258792
10°	184973
15°	156817
20°	134424
25°	113781
30°	74784
35°	53365
40°	40758
45°	23964
50°	15824
55°	11506
60°	7493
65°	6751
70°	5731
75°	4123
80°	3072
85°	1996

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 23964 cd/sqm

TEST NUMBER: P701985

CATALOG NUMBER: 340-4C-20-D010 / 340-EU4C-1020-9030-4LBW1LI-CC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	189.0	13.5
10°-20°	363.2	26.0
20°-30°	392.3	28.1
30°-40°	242.3	17.3
40°-50°	121.4	8.7
50°-60°	50.9	3.6
60°-70°	23.9	1.7
70°-80°	10.5	0.8
80°-90°	2.3	0.2
90°-100°	0.2	0.0
100°-110°	0.6	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	944.5	67.6
0°-40°	1186.8	85.0
0°-60°	1359.0	97.3
0°-90°	1395.8	99.9
90°-120°	0.8	0.1
90°-150°	0.8	0.1
90°-180°	1.0	0.1
0°-180°	1396.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2794	
5°	2223	189
15°	1306	363
25°	889	392
35°	377	242
45°	146	121
55°	57	51
65°	25	24
75°	9	11
85°	2	2
90°	0	0
95°	0	1
105°	0	1
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	

TEST NUMBER: P701985

CATALOG NUMBER: 340-4C-20-D010 / 340-EU4C-1020-9030-4LBW1LI-CC

CANDELA DISTRIBUTION (FULL):

0°	
0°	2793.5
1°	2779.7
2°	2701.2
3°	2572.0
4°	2404.4
5°	2222.8
6°	2041.3
7°	1876.7
8°	1746.0
9°	1647.5
10°	1570.6
11°	1504.5
12°	1447.5
13°	1398.3
14°	1353.7
15°	1306.0
16°	1258.3
17°	1204.5
18°	1155.3
19°	1115.3
20°	1089.1
21°	1067.6
22°	1039.9
23°	1001.4
24°	949.1
25°	889.1
27.5°	715.3
30°	558.4
32.5°	450.7
35°	376.9
37.5°	323.0
40°	269.2
42.5°	201.5
45°	146.1
47.5°	110.8
50°	87.7
52.5°	72.3
55°	56.9
57.5°	40.0
60°	32.3
62.5°	27.7
65°	24.6
67.5°	20.0
70°	16.9
72.5°	12.3

TEST NUMBER: P701985

CATALOG NUMBER: 340-4C-20-D010 / 340-EU4C-1020-9030-4LBW1LI-CC

CANDELA DISTRIBUTION (continued):

	0°
75°	9.2
77.5°	7.7
80°	4.6
82.5°	3.1
85°	1.5
87.5°	1.5
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	1.5
102.5°	1.5
105°	0.0
107.5°	0.0
110°	0.0
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)