

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: SHAPER

Report Number: P702475

Luminaire Tested: 340-6C-20-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

Issue Date: 8/30/2023

Test Information

Test Method: LM-79-2019
Report Number: P702475
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-11)
Test Lab: INNOVATION CENTER
Issue Date: 8/30/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: SHAPER
Catalog Number: 340-6C-20-D010 / 340-EU4C-1020-9024-4LBW1LI-CC
Description: FARALLON 6" LED GLASS DOWNLIGHT. CYLINDRICAL CLEAR GLASS KIT.
Light Source: 2400K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1259.5 lumens
Efficiency: N/A
Efficacy: 57.8 lumens/watt
Spacing Criteria (0/90/45): 0.44 / 0.44 / 0.71
Luminous Opening: Circular (Dia: 0.46' x H: 0')
CIE Type: Direct

Input Watts (W): 21.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P702475

CATALOG NUMBER: 340-6C-20-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

Luminous Intensity Polar Plot



TEST NUMBER: P702475

CATALOG NUMBER: 340-6C-20-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97	96	94	93
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91	89	87	85
3	101	95	89	85	99	93	88	84	90	86	83		88	85	82		86	83	80	79
4	96	88	82	78	94	87	81	77	85	80	76		83	79	75		81	77	74	73
5	91	82	76	71	89	81	75	71	79	74	70		78	73	70		76	72	69	68
6	86	77	71	66	85	76	70	66	74	69	65		73	68	65		72	68	64	63
7	82	72	66	61	80	71	65	61	70	65	61		69	64	61		68	63	60	59
8	78	68	62	57	76	67	61	57	66	61	57		65	60	57		64	60	56	55
9	74	64	58	54	73	63	58	54	62	57	53		62	57	53		61	56	53	52
10	70	60	54	50	69	60	54	50	59	54	50		58	53	50		58	53	50	49

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	143060
5°	116808
10°	85591
15°	73911
20°	63297
25°	58517
30°	47166
35°	30623
40°	23157
45°	12926
50°	7521
55°	4993
60°	3406
65°	2115
70°	1831
75°	1386
80°	1014
85°	1048

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 12926 cd/sqm

TEST NUMBER: P702475

CATALOG NUMBER: 340-6C-20-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	154.2	12.2
10°-20°	306.2	24.3
20°-30°	362.0	28.7
30°-40°	253.3	20.1
40°-50°	118.2	9.4
50°-60°	41.0	3.3
60°-70°	15.6	1.2
70°-80°	6.3	0.5
80°-90°	1.5	0.1
90°-100°	1.0	0.1
100°-110°	0.6	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	822.5	65.3
0°-40°	1075.8	85.4
0°-60°	1235.0	98.1
0°-90°	1258.4	99.9
90°-120°	1.5	0.1
90°-150°	1.5	0.1
90°-180°	2.0	0.2
0°-180°	1259.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2193	
5°	1784	154
15°	1094	306
25°	813	362
35°	384	253
45°	140	118
55°	44	41
65°	14	16
75°	6	6
85°	1	1
90°	0	0
95°	0	1
105°	0	1
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0

TEST NUMBER: P702475

CATALOG NUMBER: 340-6C-20-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

CANDELA DISTRIBUTION (FULL):

0°	
0°	2192.8
2.5°	2084.3
5°	1783.6
7.5°	1487.0
10°	1292.0
12.5°	1176.7
15°	1094.3
17.5°	1020.2
20°	911.7
22.5°	830.7
25°	812.9
27.5°	744.2
30°	626.1
32.5°	492.9
35°	384.5
37.5°	314.4
40°	271.9
42.5°	211.5
45°	140.1
47.5°	97.5
50°	74.1
52.5°	56.3
55°	43.9
57.5°	34.3
60°	26.1
62.5°	19.2
65°	13.7
67.5°	12.4
70°	9.6
72.5°	8.2
75°	5.5
77.5°	4.1
80°	2.7
82.5°	1.4
85°	1.4
87.5°	1.4
90°	0.0
92.5°	0.0
95°	0.0
97.5°	1.4
100°	1.4
102.5°	1.4
105°	0.0
107.5°	0.0
110°	0.0

TEST NUMBER: P702475

CATALOG NUMBER: 340-6C-20-D010 / 340-EU4C-1020-9024-4LBW1LI-CC

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)