

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: SHAPER

Report Number: P702593

Luminaire Tested: 340-6C-30-D010 / 340-EU4C-3040-9024-4LBW1LI-GFF

Issue Date: 8/30/2023

Test Information

Test Method: LM-79-2019
Report Number: P702593
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-14)
Test Lab: INNOVATION CENTER
Issue Date: 8/30/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: SHAPER
Catalog Number: 340-6C-30-D010 / 340-EU4C-3040-9024-4LBW1LI-GFF
Description: FARALLON 6" LED GLASS DOWNLIGHT. GLASS-IN-A-GLASS, FROSTED INSIDE, FROSTED OUTSIDE KIT.
Light Source: 2400K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1658.9 lumens
Efficiency: N/A
Efficacy: 52.5 lumens/watt
Spacing Criteria (0/90/45): 0.53 / 0.53 / 0.63
Luminous Opening: Vertical Cylinder (Dia: 0.46' x H: 0.49')
CIE Type: Direct

Input Watts (W): 31.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P702593

CATALOG NUMBER: 340-6C-30-D010 / 340-EU4C-3040-9024-4LBW1LI-GFF

Luminous Intensity Polar Plot



TEST NUMBER: P702593

CATALOG NUMBER: 340-6C-30-D010 / 340-EU4C-3040-9024-4LBW1LI-GFF

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	118	118	118	118	115	115	115	115	109	109	109		104	104	104		99	99	99	96
1	107	102	97	93	104	99	95	91	94	91	88		90	87	84		85	83	81	79
2	98	89	82	77	95	87	81	75	83	78	73		79	75	71		76	72	69	66
3	90	79	71	65	87	77	70	64	74	68	62		71	65	61		68	63	59	57
4	83	71	63	56	80	70	62	56	67	60	54		64	58	53		61	56	52	50
5	77	65	56	49	75	63	55	49	61	54	48		58	52	47		56	51	47	44
6	72	59	50	44	70	58	50	44	56	49	43		54	47	43		52	46	42	40
7	67	54	46	40	65	53	45	40	51	44	39		50	43	39		48	43	38	36
8	63	50	42	37	61	49	42	36	48	41	36		46	40	36		45	39	35	33
9	60	47	39	34	58	46	39	34	45	38	33		43	37	33		42	37	33	31
10	56	44	36	31	55	43	36	31	42	35	31		41	35	31		40	34	30	29

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	93503
5°	82931
10°	69116
15°	38681
20°	25853
25°	19972
30°	16145
35°	13462
40°	11996
45°	11001
50°	10034
55°	8999
60°	8029
65°	6941
70°	5952
75°	5041
80°	4277
85°	3570

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 11001 cd/sqm

TEST NUMBER: P702593

CATALOG NUMBER: 340-6C-30-D010 / 340-EU4C-3040-9024-4LBW1LI-GFF

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	131.7	7.9
10°-20°	229.4	13.8
20°-30°	210.4	12.7
30°-40°	209.2	12.6
40°-50°	217.3	13.1
50°-60°	208.9	12.6
60°-70°	174.7	10.5
70°-80°	128.9	7.8
80°-90°	87.2	5.3
90°-100°	50.6	3.0
100°-110°	10.5	0.6
110°-120°	0.3	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	571.5	34.5
0°-40°	780.7	47.1
0°-60°	1206.8	72.7
0°-90°	1597.6	96.3
90°-120°	61.4	3.7
90°-150°	61.4	3.7
90°-180°	61.0	3.7
0°-180°	1658.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1433	
5°	1417	132
15°	781	229
25°	453	210
35°	330	209
45°	281	217
55°	233	209
65°	176	175
75°	122	129
85°	79	69
90°	63	35
95°	49	34
105°	8	11
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0

TEST NUMBER: P702593

CATALOG NUMBER: 340-6C-30-D010 / 340-EU4C-3040-9024-4LBW1LI-GFF

CANDELA DISTRIBUTION (FULL):

0°	
0°	1433.2
2.5°	1431.2
5°	1417.0
7.5°	1384.6
10°	1293.5
12.5°	1044.5
15°	781.4
17.5°	641.7
20°	556.7
22.5°	498.0
25°	453.4
27.5°	417.0
30°	382.6
32.5°	352.2
35°	330.0
37.5°	313.8
40°	301.6
42.5°	291.5
45°	281.4
47.5°	271.3
50°	259.1
52.5°	247.0
55°	232.8
57.5°	220.6
60°	206.5
62.5°	190.3
65°	176.1
67.5°	161.9
70°	147.8
72.5°	133.6
75°	121.5
77.5°	109.3
80°	99.2
82.5°	89.1
85°	78.9
87.5°	70.8
90°	62.8
92.5°	56.7
95°	48.6
97.5°	36.4
100°	24.3
102.5°	14.2
105°	8.1
107.5°	4.0
110°	2.0

TEST NUMBER: P702593

CATALOG NUMBER: 340-6C-30-D010 / 340-EU4C-3040-9024-4LBW1LI-GFF

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)