

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: SHAPER

Report Number: P702599

Luminaire Tested: 340-6C-30-D010 / 340-EU4C-3040-9027-4LBW1LI-GFC

Issue Date: 8/30/2023

Test Information

Test Method: LM-79-2019
Report Number: P702599
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-15)
Test Lab: INNOVATION CENTER
Issue Date: 8/30/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: SHAPER
Catalog Number: 340-6C-30-D010 / 340-EU4C-3040-9027-4LBW1LI-GFC
Description: FARALLON 6" LED GLASS DOWNLIGHT. GLASS-IN-A-GLASS, FROSTED INSIDE, CLEAR OUTSIDE C
KIT.
Light Source: 2700K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2023.3 lumens
Efficiency: N/A
Efficacy: 64.0 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.74
Luminous Opening: Vertical Cylinder (Dia: 0.46' x H: 0.49')
CIE Type: Direct

Input Watts (W): 31.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P702599

CATALOG NUMBER: 340-6C-30-D010 / 340-EU4C-3040-9027-4LBW1LI-GFC

Luminous Intensity Polar Plot



TEST NUMBER: P702599

CATALOG NUMBER: 340-6C-30-D010 / 340-EU4C-3040-9027-4LBW1LI-GFC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	110	110	110		105	105	105		100	100	100	98
1	109	105	101	97	106	102	99	96	98	95	92		94	91	89		90	88	86	84
2	101	93	87	82	98	91	86	81	88	83	79		84	80	77		81	78	75	73
3	93	84	76	71	91	82	75	70	79	73	69		76	71	67		73	69	66	64
4	86	76	68	62	84	74	67	61	72	65	60		69	64	60		67	62	59	57
5	81	69	61	55	78	68	60	55	66	59	54		64	58	53		62	57	53	51
6	75	63	55	50	73	62	55	49	60	54	49		59	53	48		57	52	48	46
7	71	58	51	45	69	58	50	45	56	49	44		54	49	44		53	48	44	42
8	66	54	47	41	65	54	46	41	52	46	41		51	45	41		50	44	40	38
9	63	51	43	38	61	50	43	38	49	42	38		48	42	37		47	41	37	36
10	59	47	40	35	58	47	40	35	46	39	35		45	39	35		44	38	35	33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	114236
5°	102613
10°	88523
15°	55814
20°	39859
25°	30610
30°	24661
35°	20744
40°	18304
45°	15653
50°	12563
55°	9784
60°	7695
65°	6078
70°	4913
75°	3912
80°	3174
85°	2497

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 15653 cd/sqm

TEST NUMBER: P702599

CATALOG NUMBER: 340-6C-30-D010 / 340-EU4C-3040-9027-4LBW1LI-GFC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	164.8	8.1
10°-20°	325.4	16.1
20°-30°	322.4	15.9
30°-40°	321.2	15.9
40°-50°	306.6	15.2
50°-60°	228.8	11.3
60°-70°	155.2	7.7
70°-80°	101.1	5.0
80°-90°	61.4	3.0
90°-100°	32.0	1.6
100°-110°	4.3	0.2
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	812.7	40.2
0°-40°	1133.9	56.0
0°-60°	1669.3	82.5
0°-90°	1987.0	98.2
90°-120°	36.3	1.8
90°-150°	36.3	1.8
90°-180°	36.0	1.8
0°-180°	2023.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1751	
5°	1753	165
15°	1128	325
25°	695	322
35°	508	321
45°	400	307
55°	253	229
65°	154	155
75°	94	101
85°	55	49
90°	41	23
95°	30	21
105°	2	4
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0

TEST NUMBER: P702599

CATALOG NUMBER: 340-6C-30-D010 / 340-EU4C-3040-9027-4LBW1LI-GFC

CANDELA DISTRIBUTION (FULL):

0°	
0°	1751.0
2.5°	1753.3
5°	1753.3
7.5°	1739.5
10°	1656.7
12.5°	1401.3
15°	1127.5
17.5°	973.3
20°	858.3
22.5°	766.2
25°	694.9
27.5°	635.1
30°	584.4
32.5°	540.7
35°	508.5
37.5°	483.2
40°	460.2
42.5°	434.9
45°	400.4
47.5°	363.5
50°	324.4
52.5°	287.6
55°	253.1
57.5°	223.2
60°	197.9
62.5°	174.9
65°	154.2
67.5°	138.1
70°	122.0
72.5°	108.1
75°	94.3
77.5°	82.8
80°	73.6
82.5°	64.4
85°	55.2
87.5°	48.3
90°	41.4
92.5°	36.8
95°	29.9
97.5°	23.0
100°	13.8
102.5°	6.9
105°	2.3
107.5°	0.0
110°	0.0

TEST NUMBER: P702599

CATALOG NUMBER: 340-6C-30-D010 / 340-EU4C-3040-9027-4LBW1LI-GFC

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)