

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: SHAPER

Report Number: P702716

Luminaire Tested: 340-6C-40-D010 / 340-EU4C-3040-9030-4LBW1LI-FF

Issue Date: 8/30/2023

Test Information

Test Method: LM-79-2019
Report Number: P702716
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-10)
Test Lab: INNOVATION CENTER
Issue Date: 8/30/2023
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: SHAPER
Catalog Number: 340-6C-40-D010 / 340-EU4C-3040-9030-4LBW1LI-FF
Description: FARALLON 6" LED GLASS DOWNLIGHT. FLARED FROSTED GLASS KIT.
Light Source: 3000K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2615.9 lumens
Efficiency: N/A
Efficacy: 55.7 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.81
Luminous Opening: Vertical Cylinder (Dia: 0.46' x H: 0.49')
CIE Type: Direct

Input Watts (W): 47
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P702716

CATALOG NUMBER: 340-6C-40-D010 / 340-EU4C-3040-9030-4LBW1LI-FF

Luminous Intensity Polar Plot



TEST NUMBER: P702716

CATALOG NUMBER: 340-6C-40-D010 / 340-EU4C-3040-9030-4LBW1LI-FF

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	118	118	118	118	115	115	115	115	110	110	110		104	104	104		99	99	99	97
1	110	106	102	99	107	103	100	97	99	96	93		94	92	90		90	89	87	85
2	102	96	90	86	100	94	89	84	90	86	82		86	83	80		83	80	78	76
3	96	87	81	76	93	86	80	75	83	77	73		80	75	72		77	73	70	68
4	90	80	73	68	88	79	72	67	76	71	66		74	69	65		71	67	64	62
5	85	74	67	62	83	73	66	61	71	65	61		69	64	60		67	62	59	57
6	80	69	62	57	78	68	61	56	66	60	56		64	59	55		63	58	54	53
7	75	64	57	52	74	64	57	52	62	56	52		60	55	51		59	54	51	49
8	71	60	53	49	70	60	53	48	58	52	48		57	52	48		56	51	47	46
9	68	57	50	45	66	56	50	45	55	49	45		54	48	45		53	48	44	43
10	64	53	47	43	63	53	47	42	52	46	42		51	46	42		50	45	42	40

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	148194
5°	131982
10°	115768
15°	102871
20°	90417
25°	75509
30°	33885
35°	18052
40°	14339
45°	11533
50°	9267
55°	7349
60°	6116
65°	5167
70°	4752
75°	4352
80°	3958
85°	3561

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 11533 cd/sqm

TEST NUMBER: P702716

CATALOG NUMBER: 340-6C-40-D010 / 340-EU4C-3040-9030-4LBW1LI-FF

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	212.2	8.1
10°-20°	583.8	22.3
20°-30°	712.0	27.2
30°-40°	301.5	11.5
40°-50°	228.8	8.7
50°-60°	173.2	6.6
60°-70°	132.3	5.1
70°-80°	110.8	4.2
80°-90°	85.8	3.3
90°-100°	57.3	2.2
100°-110°	17.0	0.6
110°-120°	1.3	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1508.0	57.6
0°-40°	1809.5	69.2
0°-60°	2211.4	84.5
0°-90°	2540.4	97.1
90°-120°	75.5	2.9
90°-150°	75.5	2.9
90°-180°	76.0	2.9
0°-180°	2615.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2272	
5°	2255	212
15°	2078	584
25°	1714	712
35°	442	301
45°	295	229
55°	190	173
65°	131	132
75°	105	111
85°	79	67
90°	66	36
95°	56	40
105°	13	17
115°	0	1
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0

TEST NUMBER: P702716

CATALOG NUMBER: 340-6C-40-D010 / 340-EU4C-3040-9030-4LBW1LI-FF

CANDELA DISTRIBUTION (FULL):

0°	
0°	2271.5
2.5°	2268.2
5°	2255.1
7.5°	2215.7
10°	2166.6
12.5°	2124.0
15°	2078.1
17.5°	2022.3
20°	1947.0
22.5°	1855.2
25°	1714.2
27.5°	1337.3
30°	803.0
32.5°	527.7
35°	442.5
37.5°	396.6
40°	360.5
42.5°	327.8
45°	295.0
47.5°	265.5
50°	239.3
52.5°	213.1
55°	190.1
57.5°	173.7
60°	157.3
62.5°	140.9
65°	131.1
67.5°	124.6
70°	118.0
72.5°	111.4
75°	104.9
77.5°	98.3
80°	91.8
82.5°	85.2
85°	78.7
87.5°	72.1
90°	65.6
92.5°	62.3
95°	55.7
97.5°	42.6
100°	32.8
102.5°	22.9
105°	13.1
107.5°	9.8
110°	3.3

TEST NUMBER: P702716

CATALOG NUMBER: 340-6C-40-D010 / 340-EU4C-3040-9030-4LBW1LI-FF

CANDELA DISTRIBUTION (continued):

	0°
112.5°	3.3
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)