

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: STREETWORKS

Report Number: P691463

Luminaire Tested: **CRTK2-C016-5TLD-U-T5R-7050-U0**

Issue Date: 6/13/2023

**Test Information**

Test Method: LM-79-08  
Report Number: P691463  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2301-903-19)  
Test Lab: INNOVATION CENTER  
Issue Date: 6/13/2023  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: STREETWORKS  
Catalog Number: CRTK2-C016-5TLD-U-T5R-7050-U0  
Description: CARETAKER AREA AND ROADWAY LUMINAIRE  
(1) 70 CRI, 5000K LED WITH TYPE V ROUND OPTIC AND UO SHIELD  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6589.9 lumens  
Efficiency: N/A  
Efficacy: 154.0 lumens/watt  
Luminous Opening: Circular (Dia: 0.33' x H: 0')  
IES Classification: Type V - Short  
BUG Rating: B3 - U0 - G1


Input Watts (W): 42.8  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



REPORT NUMBER: P691463  
 CATALOG NUMBER: CRTK2-C016-5TLD-U-T5R-7050-U0

### Iso-Footcandle Lines of Horizontal Illumination


× Max cd  
 - - - 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 1 fc  
 Type V - Short - N/A

REPORT NUMBER: P691463  
CATALOG NUMBER: CRTK2-C016-5TLD-U-T5R-7050-U0

### Luminous Intensity Polar Plot



— Vertical Plane Through 0-Deg Lateral      - - - Horizontal Cone Through 67.5-Deg Vertical

REPORT NUMBER: P691463

CATALOG NUMBER: CRTK2-C016-5TLD-U-T5R-7050-U0


**FLUX DISTRIBUTION:**

		Downward	Upward	Total
<b>House Side</b>	Lumens	3295.0	0.0	3295.0
	% Fixture	50.0	0.0	50.0
<b>Street Side</b>	Lumens	3295.0	0.0	3295.0
	% Fixture	50.0	0.0	50.0
<b>Total</b>	Lumens	6589.9	0.0	6589.9
	% Fixture	100.0	0.0	100.0

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	57.4	0.9
10°-20°	155.5	2.4
20°-30°	268.0	4.1
30°-40°	455.1	6.9
40°-50°	802.9	12.2
50°-60°	1368.3	20.8
60°-70°	1968.1	29.9
70°-80°	1431.2	21.7
80°-90°	83.5	1.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	6589.9	100.0
0°-180°	6589.9	100.0

**Coefficient of Utilization**




REPORT NUMBER: P691463  
 CATALOG NUMBER: CRTK2-C016-5TLD-U-T5R-7050-U0

**LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:**

Zone	Lumens	% Fixture	Zone Rating/Lumen Limit		
			B	U	G
FL (0°-30°)	240.5	3.6			
FM (30°-60°)	1313.1	19.9			
FH (60°-80°)	1699.6	25.8			G1/1800
FVH (80°-90°)	41.8	0.6			G1/100
BL (0°-30°)	240.5	3.6	B1/500		
BM (30°-60°)	1313.1	19.9	B2/2500		
BH (60°-80°)	1699.6	25.8	B3/2500		G1/1800
BVH (80°-90°)	41.8	0.6			G1/100
UL (90°-100°)	0.0	0.0		U0/0	
UH (100°-180°)	0.0	0.0		U0/0	

**BUG Rating: B3-U0-G1**

Type V Short



REPORT NUMBER: P691463  
CATALOG NUMBER: CRTK2-C016-5TLD-U-T5R-7050-U0

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	640.9
2.5°	630.5
5°	618.0
7.5°	595.1
10°	570.2
12.5°	553.5
15°	545.2
17.5°	543.1
20°	545.2
22.5°	555.6
25°	572.3
27.5°	595.1
30°	622.2
32.5°	659.7
35°	711.7
37.5°	776.2
40°	842.8
42.5°	923.9
45°	1019.7
47.5°	1132.0
50°	1254.8
52.5°	1385.9
55°	1523.2
57.5°	1652.2
60°	1783.3
62.5°	1904.0
65°	2045.5
67.5°	2103.8
70°	1958.1
72.5°	1733.4
75°	1444.2
77.5°	1042.5
80°	466.1
82.5°	60.3
85°	12.5
87.5°	2.1
90°	0.0

(END OF REPORT)