

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P957345

Luminaire Tested: **GLAN-SB9D-722-U-T4W**

Issue Date: 1/21/2025

Test Information

Test Method: LM-79-08
Report Number: P957345
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2411-289-1)
Test Lab: INNOVATION CENTER
Issue Date: 1/21/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: GLAN-SB9D-722-U-T4W
Description: GALLEON AREA AND ROADWAY HIGH DENSITY LED LUMINAIRE
(9) 70 CRI, 2200K, 900mA LIGHTSQUARES WITH 26 LEDS EACH AND TYPE IV WIDE OPTICS
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 76418 lumens
Efficiency: N/A
Efficacy: 116.1 lumens/watt
Luminous Opening: Rectangular (W 1.5' x L: 1.5' x H: 0')
IES Classification: Type IV - Short
BUG Rating: B4 - U0 - G5

Input Watts (W): 658
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




REPORT NUMBER: P957345

CATALOG NUMBER: GLAN-SB9D-722-U-T4W

Iso-Footcandle Lines of Horizontal Illumination

✕ Max cd


--- 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 15.3 fc

Type IV - Short - N/A

REPORT NUMBER: P957345
CATALOG NUMBER: GLAN-SB9D-722-U-T4W



REPORT NUMBER: P957345

CATALOG NUMBER: GLAN-SB9D-722-U-T4W

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	17275.5	0.0	17275.5
	% Fixture	22.6	0.0	22.6
Street Side	Lumens	59142.5	0.0	59142.5
	% Fixture	77.4	0.0	77.4
Total	Lumens	76418.0	0.0	76418.0
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	784.6	1.0
10°-20°	2616.1	3.4
20°-30°	4550.8	6.0
30°-40°	6523.8	8.5
40°-50°	9185.9	12.0
50°-60°	14070.1	18.4
60°-70°	20382.7	26.7
70°-80°	16276.8	21.3
80°-90°	2027.2	2.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	76418.0	100.0
0°-180°	76418.0	100.0

Coefficient of Utilization



REPORT NUMBER: P957345


CATALOG NUMBER: GLAN-SB9D-722-U-T4W

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit		
				B	U	G
FL	(0°-30°)	4273.4	5.6			
FM	(30°-60°)	21645.6	28.3			
FH	(60°-80°)	31769.2	41.6			G5
FVH	(80°-90°)	1454.3	1.9			G5
BL	(0°-30°)	3678.1	4.8	B4/5000		
BM	(30°-60°)	8134.3	10.6	B4/8500		
BH	(60°-80°)	4890.2	6.4	B4/5000		G4/5000
BVH	(80°-90°)	572.9	0.7			G4/750
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B4-U0-G5

Type IV Short



REPORT NUMBER: P957345

CATALOG NUMBER: GLAN-SB9D-722-U-T4W

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	46°	55°	65°	75°
0°	7709.1	7709.1	7709.1	7709.1	7709.1	7709.1	7709.1	7709.1	7709.1	7709.1
2.5°	8011.0	8063.3	8015.0	7970.8	7950.6	7898.3	7894.3	7862.1	7841.9	7785.6
5°	8570.6	8639.0	8558.5	8469.9	8389.4	8260.6	8244.5	8151.9	8047.2	7926.5
7.5°	9202.6	9263.0	9170.4	9037.5	8896.7	8683.3	8679.3	8510.2	8345.1	8139.8
10°	9754.1	9834.6	9709.8	9528.7	9351.5	9110.0	9081.8	8888.6	8679.3	8413.6
12.5°	10241.2	10297.6	10176.8	9955.4	9750.1	9508.5	9472.3	9259.0	9025.5	8723.5
15°	10627.7	10700.1	10539.1	10301.6	10084.2	9846.7	9814.5	9621.3	9387.8	9069.8
17.5°	10881.3	10941.7	10776.6	10510.9	10301.6	10104.3	10080.2	9919.2	9713.9	9391.8
20°	10977.9	11042.3	10869.2	10599.5	10406.3	10253.3	10241.2	10124.5	9983.6	9689.7
22.5°	11074.5	11134.9	10909.5	10627.7	10458.6	10362.0	10358.0	10281.5	10225.1	9983.6
25°	11465.0	11481.1	11179.2	10772.6	10531.1	10446.5	10442.5	10438.5	10462.6	10273.4
27.5°	11803.2	11799.1	11541.5	11159.1	10784.7	10607.5	10603.5	10643.8	10720.3	10563.3
30°	12298.3	12254.0	11948.1	11549.5	11207.4	10933.6	10909.5	10873.2	10933.6	10808.8
32.5°	13349.0	13208.1	12713.0	12004.4	11557.6	11348.3	11316.1	11090.6	11114.8	11038.3
35°	14854.6	14669.4	14009.2	12865.9	11992.4	11694.5	11678.4	11392.5	11344.2	11275.8
37.5°	16646.0	16416.5	15647.6	14113.9	12741.1	12097.0	12072.9	11815.2	11618.0	11545.5
40°	18445.5	18155.6	17519.6	15635.6	13844.2	12769.3	12692.8	12302.3	12076.9	11956.1
42.5°	20192.6	19951.0	19407.6	17342.4	15204.8	13751.6	13582.5	12914.2	12745.2	12632.4
45°	21738.4	21521.0	21122.5	19166.0	16799.0	15088.1	14923.0	13832.1	13779.7	13779.7
47.5°	22994.4	22946.1	22523.4	21025.9	18678.9	16609.8	16323.9	15108.2	15249.1	15466.5
50°	24387.3	24254.4	23803.6	22857.5	20889.0	18352.9	18119.4	16674.2	17201.5	17797.3
52.5°	25667.4	25739.9	25236.7	24765.7	23384.9	20297.2	19886.6	18521.9	19661.2	20647.5
55°	26983.8	26987.8	26847.0	26782.5	26001.6	22446.9	21996.1	20744.1	22555.6	23779.4
57.5°	28219.7	28227.7	28437.1	29004.7	29036.9	24926.7	24415.5	23473.5	25772.1	27020.1
60°	29322.7	29379.1	29950.7	31279.2	31705.9	27768.8	27285.7	26698.0	29097.3	30353.3
62.5°	29693.1	29898.4	31170.5	33058.5	34342.7	31255.0	30780.0	30429.8	32591.5	33759.0
65°	29065.1	29536.1	31995.7	34527.9	37056.0	35397.4	34926.4	34544.0	36222.7	37321.7
67.5°	27523.3	28131.1	31947.4	36069.7	40348.9	40381.1	39942.3	39044.6	40115.4	40538.1
70°	23461.4	24371.2	29133.5	36645.3	44129.0	47196.5	46773.8	44463.1	44000.2	41955.2
72.5°	15116.3	16340.0	21452.6	31907.2	44970.4	53609.4	53585.2	49354.3	45228.0	39201.6
75°	5515.1	6263.9	9967.5	20027.5	37748.4	53283.3	53440.3	48516.9	41286.9	30280.8
77.5°	2008.8	2198.0	3252.7	7697.0	23215.8	42752.2	43078.3	38787.0	29387.1	15196.8
80°	1054.7	1159.4	1666.6	2987.0	9947.3	25389.7	25900.9	23050.8	13811.9	4577.1
82.5°	583.7	632.0	933.9	1622.3	4480.5	10857.1	11163.1	9106.0	4858.9	1940.4
85°	314.0	334.1	438.8	885.6	2189.9	3764.0	3848.5	2721.3	1936.3	1139.3
87.5°	92.6	112.7	144.9	281.8	857.5	845.4	865.5	539.4	764.9	575.7
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P957345

CATALOG NUMBER: GLAN-SB9D-722-U-T4W

CANDELA DISTRIBUTION (continued):

85°		90°	95°	105°	115°	125°	135°	145°	155°	165°	175°
7709.1	0°	7709.1	7709.1	7709.1	7709.1	7709.1	7709.1	7709.1	7709.1	7709.1	7709.1
7769.5	2.5°	7745.3	7733.2	7689.0	7668.8	7644.7	7640.7	7660.8	7664.8	7668.8	7672.9
7858.0	5°	7817.8	7777.5	7737.3	7713.1	7721.2	7725.2	7765.4	7793.6	7813.8	7829.9
8023.1	7.5°	7958.7	7926.5	7858.0	7854.0	7866.1	7902.3	7954.7	8019.1	8055.3	8083.5
8236.4	10°	8168.0	8107.6	8027.1	8039.2	8063.3	8115.7	8224.4	8276.7	8337.1	8389.4
8498.1	12.5°	8381.4	8329.0	8236.4	8244.5	8284.8	8377.3	8482.0	8546.4	8586.7	8626.9
8779.9	15°	8659.1	8566.5	8465.9	8465.9	8538.4	8639.0	8687.3	8739.7	8763.8	8808.1
9081.8	17.5°	8945.0	8824.2	8691.3	8683.3	8771.9	8820.2	8848.3	8856.4	8864.4	8912.8
9375.7	20°	9230.8	9097.9	8908.7	8892.6	8912.8	8904.7	8900.7	8892.6	8904.7	8965.1
9677.6	22.5°	9512.6	9359.6	9097.9	9025.5	8969.1	8892.6	8888.6	8884.6	8892.6	8953.0
10003.7	25°	9842.7	9657.5	9307.3	9089.9	8900.7	8796.0	8808.1	8812.1	8820.2	8868.5
10341.9	27.5°	10201.0	9995.6	9500.5	9069.8	8727.6	8655.1	8635.0	8647.1	8675.2	8751.7
10680.0	30°	10559.2	10317.7	9677.6	8989.2	8510.2	8409.5	8345.1	8373.3	8461.9	8538.4
10973.9	32.5°	10885.3	10643.8	9818.5	8812.1	8232.4	8075.4	7990.9	8027.1	8115.7	8143.9
11300.0	35°	11267.7	10994.0	9878.9	8530.3	7930.5	7689.0	7576.2	7523.9	7568.2	7540.0
11682.4	37.5°	11694.5	11408.6	9870.9	8160.0	7576.2	7298.5	7141.5	6944.2	6851.6	6755.0
12246.0	40°	12326.5	11915.9	9774.2	7713.1	7137.4	6883.8	6602.0	6267.9	6058.6	5869.4
13155.8	42.5°	13188.0	12620.4	9597.1	7222.0	6642.3	6404.8	6022.3	5631.9	5301.8	4987.8
14536.6	45°	14472.2	13542.2	9375.7	6698.7	6106.9	5873.4	5458.8	5020.0	4645.6	4243.0
16497.0	47.5°	16323.9	14782.1	9166.4	6102.9	5543.3	5329.9	4955.6	4549.0	4106.1	3715.7
19331.1	50°	18868.1	16561.5	8973.1	5523.2	4987.8	4826.7	4528.8	4114.2	3667.4	3353.4
22652.2	52.5°	22104.8	18980.9	8892.6	4963.6	4468.5	4408.1	4170.6	3784.1	3361.4	3095.7
26524.9	55°	25820.4	21875.3	8892.6	4428.2	4013.6	4033.7	3868.6	3510.4	3144.0	2906.5
30518.3	57.5°	29612.6	24806.0	8731.6	3933.0	3627.1	3711.6	3607.0	3293.0	2962.9	2717.3
34717.1	60°	33106.8	27261.6	8079.4	3482.2	3284.9	3417.8	3349.3	3079.6	2677.0	2471.7
38227.4	62.5°	35791.9	28646.4	6823.4	3123.9	3003.1	3156.1	3119.9	2797.8	2624.7	2540.2
41109.8	65°	37136.5	28421.0	5217.2	2805.9	2765.6	3003.1	2926.6	2914.6	2777.7	2681.1
42047.7	67.5°	36311.2	26480.6	3784.1	2572.4	2628.7	2862.2	3156.1	3204.4	2950.8	2761.6
39406.9	70°	32692.2	22970.3	2817.9	2351.0	2455.6	2866.3	3598.9	3353.4	2894.4	2673.0
31605.3	72.5°	24870.4	17129.1	2185.9	2117.5	2230.2	2886.4	3796.2	3284.9	2733.4	2954.8
19689.4	75°	14222.6	9403.9	1755.2	1831.7	1948.4	2697.2	3695.5	3107.8	2608.6	2713.3
7801.7	77.5°	5422.5	3615.0	1449.2	1549.9	1566.0	2355.0	3534.5	3095.7	2483.8	2423.4
2338.9	80°	1880.0	1413.0	1199.6	1231.8	1211.7	2093.3	3389.6	2693.1	2032.9	1819.6
966.2	82.5°	768.9	704.5	950.0	909.8	861.5	1626.4	2737.4	2202.0	1662.6	1469.4
467.0	85°	334.1	446.8	628.0	551.5	499.2	1127.2	2194.0	1863.9	1404.9	1211.7
153.0	87.5°	68.4	169.1	265.7	249.6	257.6	752.8	1557.9	1324.4	994.3	744.7
0.0	90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END O

180°
7709.1
7689.0
7837.9
8091.5
8377.3
8643.0
8824.2
8928.9
8989.2
8993.3
8932.9
8828.2
8622.9
8244.5
7628.6
6815.4
5881.5
4959.6
4194.7
3671.4
3333.2
3075.6
2882.4
2677.0
2439.5
2512.0
2648.9
2729.4
2636.8
2930.7
2713.3
2210.1
1759.2
1453.3
1207.7
583.7
0.0

F REPORT)