

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P868239

Luminaire Tested: **MEM2-HSN-SA-150-722-U-5WQ**

Issue Date: 08/21/2024



Test Information

Test Method: LM-79-08
Report Number: P868239
Test Lab: INNOVATION CENTER(G3)
Issue Date: 08/21/2024
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: MEM2-HSN-SA-150-722-U-5WQ
Description: EPIC MODERN SHORT HOUSING DISCRETE LED ARRAYS 150W 70CRI 2200K
FITXURE w/ TYPE V SQUARE WIDE DISTRIBUTION OPTIC
Light Source: (30) 2200K CCT, 70 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 16950.4 lumens
Efficiency: N/A
Efficacy: 126.5 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 0.33' x H: 0')
IES Classification: Type V - Short
BUG Rating: B4 - U0 - G2

Input Watts (W): 134
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: 0.99
Total Harmonic Distortion (THDi): 6.70%
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

REPORT NUMBER: P868239
 CATALOG NUMBER: MEM2-HSN-SA-150-722-U-5WQ

Iso-Footcandle Lines of Horizontal Illumination


× Max cd
 - - - 1/2 Max cd



Based on 20 foot mounting height. Maximum calculated value = 3 fc
 Type V - Short - N/A

REPORT NUMBER: P868239
CATALOG NUMBER: MEM2-HSN-SA-150-722-U-5WQ

Luminous Intensity Polar Plot



— Vertical Plane Through 45-Deg Lateral - - - Horizontal Cone Through 72.5-Deg Vertical

REPORT NUMBER: P868239
 CATALOG NUMBER: MEM2-HSN-SA-150-722-U-5WQ

FLUX DISTRIBUTION:

| | | Downward | Upward | Total |
|--------------------|-----------|----------|--------|---------|
| House Side | Lumens | 8475.2 | 0.0 | 8475.2 |
| | % Fixture | 50.0 | 0.0 | 50.0 |
| Street Side | Lumens | 8475.2 | 0.0 | 8475.2 |
| | % Fixture | 50.0 | 0.0 | 50.0 |
| Total | Lumens | 16950.4 | 0.0 | 16950.4 |
| | % Fixture | 100.0 | 0.0 | 100.0 |

Coefficient of Utilization

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|---------|-----------|
| 0°-10° | 107.2 | 0.6 |
| 10°-20° | 358.0 | 2.1 |
| 20°-30° | 738.5 | 4.4 |
| 30°-40° | 1359.6 | 8.0 |
| 40°-50° | 2390.6 | 14.1 |
| 50°-60° | 3467.2 | 20.5 |
| 60°-70° | 4519.9 | 26.7 |
| 70°-80° | 3757.1 | 22.2 |
| 80°-90° | 252.3 | 1.5 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-90° | 16950.4 | 100.0 |
| 0°-180° | 16950.4 | 100.0 |



REPORT NUMBER: P868239


CATALOG NUMBER: MEM2-HSN-SA-150-722-U-5WQ

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

| Zone | Lumens | % Fixture | Zone Rating/Lumen Limit | | |
|----------------|--------|-----------|-------------------------|------|---------|
| | | | B | U | G |
| FL (0°-30°) | 601.9 | 3.6 | | | |
| FM (30°-60°) | 3608.7 | 21.3 | | | |
| FH (60°-80°) | 4138.5 | 24.4 | | | G2/5000 |
| FVH (80°-90°) | 126.1 | 0.7 | | | G2/225 |
| BL (0°-30°) | 601.9 | 3.6 | B2/1000 | | |
| BM (30°-60°) | 3608.7 | 21.3 | B3/5000 | | |
| BH (60°-80°) | 4138.5 | 24.4 | B4/5000 | | G2/5000 |
| BVH (80°-90°) | 126.1 | 0.7 | | | G2/225 |
| UL (90°-100°) | 0.0 | 0.0 | | U0/0 | |
| UH (100°-180°) | 0.0 | 0.0 | | U0/0 | |

BUG Rating: B4-U0-G2

Type V Short





REPORT NUMBER: P868239

CATALOG NUMBER: MEM2-HSN-SA-150-722-U-5WQ

CANDELA DISTRIBUTION (FULL):

| | 0° | 5° | 15° | 25° | 35° | 45° | 55° | 65° | 75° | 85° | 90° |
|-------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0° | 1119.0 | 1119.0 | 1119.0 | 1119.0 | 1119.0 | 1119.0 | 1119.0 | 1119.0 | 1119.0 | 1119.0 | 1119.0 |
| 2.5° | 1115.5 | 1117.3 | 1117.3 | 1117.3 | 1119.0 | 1120.8 | 1122.5 | 1124.3 | 1127.8 | 1129.6 | 1129.6 |
| 5° | 1120.8 | 1119.0 | 1117.3 | 1120.8 | 1120.8 | 1120.8 | 1122.5 | 1124.3 | 1124.3 | 1124.3 | 1126.1 |
| 7.5° | 1115.5 | 1117.3 | 1115.5 | 1115.5 | 1120.8 | 1122.5 | 1120.8 | 1119.0 | 1119.0 | 1120.8 | 1120.8 |
| 10° | 1134.8 | 1133.1 | 1131.3 | 1131.3 | 1136.6 | 1138.3 | 1136.6 | 1134.8 | 1134.8 | 1138.3 | 1138.3 |
| 12.5° | 1178.8 | 1182.3 | 1171.7 | 1171.7 | 1178.8 | 1182.3 | 1177.0 | 1175.2 | 1177.0 | 1180.5 | 1180.5 |
| 15° | 1247.3 | 1245.5 | 1238.5 | 1231.5 | 1238.5 | 1243.8 | 1236.7 | 1233.2 | 1235.0 | 1243.8 | 1236.7 |
| 17.5° | 1322.8 | 1324.6 | 1317.5 | 1310.5 | 1315.8 | 1322.8 | 1312.3 | 1303.5 | 1305.2 | 1308.7 | 1305.2 |
| 20° | 1407.1 | 1405.4 | 1403.6 | 1403.6 | 1414.2 | 1422.9 | 1407.1 | 1386.0 | 1380.8 | 1377.3 | 1377.3 |
| 22.5° | 1468.6 | 1473.9 | 1475.6 | 1491.4 | 1516.0 | 1524.8 | 1503.7 | 1475.6 | 1454.6 | 1444.0 | 1437.0 |
| 25° | 1565.2 | 1560.0 | 1556.4 | 1574.0 | 1610.9 | 1626.7 | 1600.4 | 1561.7 | 1540.6 | 1538.9 | 1544.1 |
| 27.5° | 1653.1 | 1653.1 | 1660.1 | 1677.7 | 1712.8 | 1728.6 | 1705.8 | 1667.1 | 1656.6 | 1656.6 | 1651.3 |
| 30° | 1767.2 | 1762.0 | 1769.0 | 1798.9 | 1825.2 | 1835.8 | 1816.4 | 1790.1 | 1781.3 | 1781.3 | 1772.5 |
| 32.5° | 1900.8 | 1902.5 | 1913.1 | 1932.4 | 1958.7 | 1960.5 | 1953.5 | 1941.2 | 1935.9 | 1930.6 | 1939.4 |
| 35° | 2104.5 | 2104.5 | 2101.0 | 2115.1 | 2122.1 | 2125.6 | 2129.1 | 2123.9 | 2123.9 | 2123.9 | 2116.8 |
| 37.5° | 2357.5 | 2343.5 | 2341.7 | 2329.4 | 2320.6 | 2329.4 | 2345.2 | 2362.8 | 2376.8 | 2368.0 | 2364.5 |
| 40° | 2608.7 | 2601.7 | 2580.6 | 2561.3 | 2554.3 | 2557.8 | 2577.1 | 2614.0 | 2629.8 | 2629.8 | 2643.8 |
| 42.5° | 2879.2 | 2865.2 | 2838.8 | 2816.0 | 2796.7 | 2802.0 | 2819.5 | 2865.2 | 2900.3 | 2916.1 | 2909.1 |
| 45° | 3121.7 | 3109.4 | 3083.0 | 3061.9 | 3047.9 | 3046.1 | 3069.0 | 3098.8 | 3146.3 | 3160.3 | 3170.9 |
| 47.5° | 3329.0 | 3320.2 | 3297.3 | 3276.3 | 3281.5 | 3283.3 | 3290.3 | 3316.7 | 3355.3 | 3374.6 | 3372.9 |
| 50° | 3497.6 | 3490.6 | 3469.5 | 3478.3 | 3492.3 | 3506.4 | 3497.6 | 3515.2 | 3539.8 | 3548.6 | 3555.6 |
| 52.5° | 3652.2 | 3641.7 | 3627.6 | 3643.4 | 3680.3 | 3708.4 | 3713.7 | 3701.4 | 3708.4 | 3713.7 | 3708.4 |
| 55° | 3805.0 | 3792.7 | 3789.2 | 3817.3 | 3873.5 | 3926.2 | 3921.0 | 3885.8 | 3877.1 | 3866.5 | 3861.2 |
| 57.5° | 3929.8 | 3921.0 | 3935.0 | 3982.5 | 4091.4 | 4161.6 | 4138.8 | 4058.0 | 4022.9 | 3998.3 | 3991.2 |
| 60° | 4008.8 | 4007.1 | 4038.7 | 4149.3 | 4314.5 | 4412.9 | 4376.0 | 4237.2 | 4158.1 | 4135.3 | 4124.8 |
| 62.5° | 4051.0 | 4052.7 | 4108.9 | 4305.7 | 4569.2 | 4702.7 | 4637.7 | 4425.2 | 4302.2 | 4279.3 | 4282.9 |
| 65° | 4089.6 | 4084.3 | 4158.1 | 4437.4 | 4845.0 | 5025.9 | 4938.1 | 4651.8 | 4472.6 | 4426.9 | 4426.9 |
| 67.5° | 4117.7 | 4123.0 | 4233.7 | 4569.2 | 5113.8 | 5372.0 | 5243.8 | 4892.4 | 4655.3 | 4586.8 | 4578.0 |
| 70° | 3762.9 | 3813.8 | 4159.9 | 4657.0 | 5326.3 | 5677.7 | 5509.0 | 5040.0 | 4662.3 | 4467.3 | 4448.0 |
| 72.5° | 2858.2 | 2905.6 | 3654.0 | 4500.7 | 5435.3 | 5881.5 | 5607.4 | 4852.0 | 4237.2 | 3989.5 | 3915.7 |
| 75° | 1884.9 | 1918.3 | 2722.9 | 3931.5 | 5133.1 | 5688.2 | 5106.8 | 4179.2 | 3336.0 | 3014.5 | 3033.8 |
| 77.5° | 839.7 | 946.9 | 1735.6 | 3067.2 | 4228.4 | 4578.0 | 3894.6 | 2851.1 | 2037.8 | 1725.1 | 1691.7 |
| 80° | 351.3 | 384.7 | 655.3 | 1635.5 | 2450.6 | 2345.2 | 1658.3 | 955.7 | 607.8 | 472.6 | 456.7 |
| 82.5° | 101.9 | 105.4 | 130.0 | 282.8 | 498.9 | 586.7 | 353.1 | 179.2 | 170.4 | 135.3 | 124.7 |
| 85° | 7.0 | 7.0 | 10.5 | 17.6 | 24.6 | 40.4 | 45.7 | 52.7 | 59.7 | 50.9 | 50.9 |
| 87.5° | 3.5 | 3.5 | 3.5 | 5.3 | 5.3 | 7.0 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 |
| 90° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Streetworks

Report Number: SP1-2407-157-2

Test Date: 08/07/2024

Luminaire Tested: MEM2-HTN-SA-40-722-U-5WQ-2

Data in this report applies to families of products including MEM2-HTN-SA-40-722-U-5WQ-2

Test Information

Test Method: LM-79-2019
 Report Number: SP1-2407-157-2
 Test Lab: COOPER LIGHTING SOLUTIONS
 Photometer: SP1 - 76IN SPHERE
 Measurement Geometry: 4π
 Issue Date: 08/20/2024
 Manufacturer: COOPER LIGHTING SOLUTIONS
 Product Line: Streetworks
 Catalog Number: **MEM2-HTN-SA-40-722-U-5WQ-2**
 Description: Epic Modern Light Square 40W 5WQ Optic and Flare Trim

Spectral Parameters

CCT (K): 2253
 CIE u': 0.2868
 CIE v': 0.5332
 Duv: -0.0014
 CIE x: 0.4974
 CIE y: 0.4110
 CIE z: 0.0915
 Peak Wavelength (nm): 603
 Dominant Wavelength (nm): 587
 Purity: 72.69432
 Rf: 76.9
 Rg: 92.7

| | | | |
|-----------|------|------|-------|
| CRI (Ra): | 70.6 | | |
| R1: | 68.4 | R9: | -36.0 |
| R2: | 88.7 | R10: | 78.2 |
| R3: | 85.4 | R11: | 61.0 |
| R4: | 63.5 | R12: | 74.2 |
| R5: | 69.0 | R13: | 72.8 |
| R6: | 88.9 | R14: | 92.2 |
| R7: | 68.5 | R15: | 58.0 |
| R8: | 32.0 | | |



Test Conditions


Stabilization Time: 29M
 Operation Time: 1H 29M
 Sphere Temperature (°C): 24.1

REPORT NUMBER: SP1-2407-157-2


| Measurement and Test Equipment | | | |
|--------------------------------|-----------------------|------------------|----------------------|
| Instrument | Identification Number | Calibration Date | Calibration Due Date |
| Photometer | IN0058 | 6/18/2024 | 12/18/2024 |
| Power Meter | INXT2011004 | 2/8/2024 | 2/8/2025 |
| AC Power Source | IN0063 | 10/24/2023 | 10/24/2024 |
| DC Power Source | IN0208 | 10/24/2023 | 10/24/2024 |
| Sphere Thermometer | IN0085 | 10/24/2023 | 10/24/2024 |
| Room Thermometer | IN0046 | 10/24/2023 | 10/24/2024 |

REPORT NUMBER: SP1-2407-157-2

CIE 1931 Chromaticity Diagram




CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



Point lies inside the ANSI 2200K 4-step quadrangle

REPORT NUMBER: SP1-2407-157-2

Photopic Flux vs. Wavelength



Photopic Lumens: NR

| λ (nm) | Power W [^] /nm | Lumens (ϕ /nm) | λ (nm) | Power W [^] /nm | Lumens (ϕ /nm) | λ (nm) | Power W [^] /nm | Lumens (ϕ /nm) | λ (nm) | Power W [^] /nm | Lumens (ϕ /nm) | λ (nm) | Power W [^] /nm | Lumens (ϕ /nm) |
|-------------------|-----------------------------|-------------------------|-------------------|-----------------------------|-------------------------|-------------------|-----------------------------|-------------------------|-------------------|-----------------------------|-------------------------|-------------------|-----------------------------|-------------------------|
| 360 | 0 | NR | 490 | 117 | NR | 620 | 896 | NR | 750 | 20 | NR | 880 | 0 | NR |
| 365 | 0 | NR | 495 | 137 | NR | 625 | 838 | NR | 755 | 17 | NR | 885 | 0 | NR |
| 370 | 0 | NR | 500 | 160 | NR | 630 | 774 | NR | 760 | 14 | NR | 890 | 0 | NR |
| 375 | 0 | NR | 505 | 183 | NR | 635 | 704 | NR | 765 | 12 | NR | 895 | 0 | NR |
| 380 | 0 | NR | 510 | 202 | NR | 640 | 635 | NR | 770 | 10 | NR | 900 | 0 | NR |
| 385 | 0 | NR | 515 | 219 | NR | 645 | 565 | NR | 775 | 9 | NR | 905 | 0 | NR |
| 390 | 0 | NR | 520 | 235 | NR | 650 | 501 | NR | 780 | 7 | NR | 910 | 0 | NR |
| 395 | 0 | NR | 525 | 249 | NR | 655 | 440 | NR | 785 | 6 | NR | 915 | 0 | NR |
| 400 | 0 | NR | 530 | 263 | NR | 660 | 383 | NR | 790 | 5 | NR | 920 | 0 | NR |
| 405 | 0 | NR | 535 | 281 | NR | 665 | 332 | NR | 795 | 5 | NR | 925 | 0 | NR |
| 410 | 1 | NR | 540 | 302 | NR | 670 | 286 | NR | 800 | 4 | NR | 930 | 0 | NR |
| 415 | 3 | NR | 545 | 331 | NR | 675 | 245 | NR | 805 | 3 | NR | 935 | 0 | NR |
| 420 | 6 | NR | 550 | 366 | NR | 680 | 210 | NR | 810 | 3 | NR | 940 | 0 | NR |
| 425 | 12 | NR | 555 | 411 | NR | 685 | 178 | NR | 815 | 3 | NR | 945 | 0 | NR |
| 430 | 21 | NR | 560 | 469 | NR | 690 | 152 | NR | 820 | 2 | NR | 950 | 0 | NR |
| 435 | 38 | NR | 565 | 536 | NR | 695 | 129 | NR | 825 | 2 | NR | 955 | 0 | NR |
| 440 | 66 | NR | 570 | 614 | NR | 700 | 109 | NR | 830 | 2 | NR | 960 | 0 | NR |
| 445 | 122 | NR | 575 | 701 | NR | 705 | 92 | NR | 835 | 1 | NR | 965 | 0 | NR |
| 450 | 215 | NR | 580 | 785 | NR | 710 | 77 | NR | 840 | 1 | NR | 970 | 0 | NR |
| 455 | 236 | NR | 585 | 863 | NR | 715 | 66 | NR | 845 | 1 | NR | 975 | 0 | NR |
| 460 | 170 | NR | 590 | 928 | NR | 720 | 55 | NR | 850 | 1 | NR | 980 | 0 | NR |
| 465 | 148 | NR | 595 | 971 | NR | 725 | 47 | NR | 855 | 1 | NR | 985 | 0 | NR |
| 470 | 132 | NR | 600 | 994 | NR | 730 | 40 | NR | 860 | 1 | NR | 990 | 0 | NR |
| 475 | 104 | NR | 605 | 996 | NR | 735 | 33 | NR | 865 | 1 | NR | 995 | 0 | NR |
| 480 | 97 | NR | 610 | 979 | NR | 740 | 28 | NR | 870 | 1 | NR | 1000 | 0 | NR |
| 485 | 105 | NR | 615 | 943 | NR | 745 | 24 | NR | 875 | 0 | NR | | | |

REPORT NUMBER: SP1-2407-157-2

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR S/P: 0.96

| λ (nm) | Power W [^] /nm | Lumens (φ/nm) | λ (nm) | Power W [^] /nm | Lumens (φ/nm) | λ (nm) | Power W [^] /nm | Lumens (φ/nm) | λ (nm) | Power W [^] /nm | Lumens (φ/nm) | λ (nm) | Power W [^] /nm | Lumens (φ/nm) |
|--------|--------------------------|---------------|--------|--------------------------|---------------|--------|--------------------------|---------------|--------|--------------------------|---------------|--------|--------------------------|---------------|
| 360 | 0 | NR | 490 | 117 | NR | 620 | 896 | NR | 750 | 20 | NR | 880 | 0 | NR |
| 365 | 0 | NR | 495 | 137 | NR | 625 | 838 | NR | 755 | 17 | NR | 885 | 0 | NR |
| 370 | 0 | NR | 500 | 160 | NR | 630 | 774 | NR | 760 | 14 | NR | 890 | 0 | NR |
| 375 | 0 | NR | 505 | 183 | NR | 635 | 704 | NR | 765 | 12 | NR | 895 | 0 | NR |
| 380 | 0 | NR | 510 | 202 | NR | 640 | 635 | NR | 770 | 10 | NR | 900 | 0 | NR |
| 385 | 0 | NR | 515 | 219 | NR | 645 | 565 | NR | 775 | 9 | NR | 905 | 0 | NR |
| 390 | 0 | NR | 520 | 235 | NR | 650 | 501 | NR | 780 | 7 | NR | 910 | 0 | NR |
| 395 | 0 | NR | 525 | 249 | NR | 655 | 440 | NR | 785 | 6 | NR | 915 | 0 | NR |
| 400 | 0 | NR | 530 | 263 | NR | 660 | 383 | NR | 790 | 5 | NR | 920 | 0 | NR |
| 405 | 0 | NR | 535 | 281 | NR | 665 | 332 | NR | 795 | 5 | NR | 925 | 0 | NR |
| 410 | 1 | NR | 540 | 302 | NR | 670 | 286 | NR | 800 | 4 | NR | 930 | 0 | NR |
| 415 | 3 | NR | 545 | 331 | NR | 675 | 245 | NR | 805 | 3 | NR | 935 | 0 | NR |
| 420 | 6 | NR | 550 | 366 | NR | 680 | 210 | NR | 810 | 3 | NR | 940 | 0 | NR |
| 425 | 12 | NR | 555 | 411 | NR | 685 | 178 | NR | 815 | 3 | NR | 945 | 0 | NR |
| 430 | 21 | NR | 560 | 469 | NR | 690 | 152 | NR | 820 | 2 | NR | 950 | 0 | NR |
| 435 | 38 | NR | 565 | 536 | NR | 695 | 129 | NR | 825 | 2 | NR | 955 | 0 | NR |
| 440 | 66 | NR | 570 | 614 | NR | 700 | 109 | NR | 830 | 2 | NR | 960 | 0 | NR |
| 445 | 122 | NR | 575 | 701 | NR | 705 | 92 | NR | 835 | 1 | NR | 965 | 0 | NR |
| 450 | 215 | NR | 580 | 785 | NR | 710 | 77 | NR | 840 | 1 | NR | 970 | 0 | NR |
| 455 | 236 | NR | 585 | 863 | NR | 715 | 66 | NR | 845 | 1 | NR | 975 | 0 | NR |
| 460 | 170 | NR | 590 | 928 | NR | 720 | 55 | NR | 850 | 1 | NR | 980 | 0 | NR |
| 465 | 148 | NR | 595 | 971 | NR | 725 | 47 | NR | 855 | 1 | NR | 985 | 0 | NR |
| 470 | 132 | NR | 600 | 994 | NR | 730 | 40 | NR | 860 | 1 | NR | 990 | 0 | NR |
| 475 | 104 | NR | 605 | 996 | NR | 735 | 33 | NR | 865 | 1 | NR | 995 | 0 | NR |
| 480 | 97 | NR | 610 | 979 | NR | 740 | 28 | NR | 870 | 1 | NR | 1000 | 0 | NR |
| 485 | 105 | NR | 615 | 943 | NR | 745 | 24 | NR | 875 | 0 | NR | | | |

REPORT NUMBER: SP1-2407-157-2

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR

M/P: 1.71

| λ (nm) | Power W [^] /nm | Lumens (φ/nm) | λ (nm) | Power W [^] /nm | Lumens (φ/nm) | λ (nm) | Power W [^] /nm | Lumens (φ/nm) | λ (nm) | Power W [^] /nm | Lumens (φ/nm) | λ (nm) | Power W [^] /nm | Lumens (φ/nm) |
|--------|--------------------------|---------------|--------|--------------------------|---------------|--------|--------------------------|---------------|--------|--------------------------|---------------|--------|--------------------------|---------------|
| 360 | 0 | NR | 490 | 117 | NR | 620 | 896 | NR | 750 | 20 | NR | 880 | 0 | NR |
| 365 | 0 | NR | 495 | 137 | NR | 625 | 838 | NR | 755 | 17 | NR | 885 | 0 | NR |
| 370 | 0 | NR | 500 | 160 | NR | 630 | 774 | NR | 760 | 14 | NR | 890 | 0 | NR |
| 375 | 0 | NR | 505 | 183 | NR | 635 | 704 | NR | 765 | 12 | NR | 895 | 0 | NR |
| 380 | 0 | NR | 510 | 202 | NR | 640 | 635 | NR | 770 | 10 | NR | 900 | 0 | NR |
| 385 | 0 | NR | 515 | 219 | NR | 645 | 565 | NR | 775 | 9 | NR | 905 | 0 | NR |
| 390 | 0 | NR | 520 | 235 | NR | 650 | 501 | NR | 780 | 7 | NR | 910 | 0 | NR |
| 395 | 0 | NR | 525 | 249 | NR | 655 | 440 | NR | 785 | 6 | NR | 915 | 0 | NR |
| 400 | 0 | NR | 530 | 263 | NR | 660 | 383 | NR | 790 | 5 | NR | 920 | 0 | NR |
| 405 | 0 | NR | 535 | 281 | NR | 665 | 332 | NR | 795 | 5 | NR | 925 | 0 | NR |
| 410 | 1 | NR | 540 | 302 | NR | 670 | 286 | NR | 800 | 4 | NR | 930 | 0 | NR |
| 415 | 3 | NR | 545 | 331 | NR | 675 | 245 | NR | 805 | 3 | NR | 935 | 0 | NR |
| 420 | 6 | NR | 550 | 366 | NR | 680 | 210 | NR | 810 | 3 | NR | 940 | 0 | NR |
| 425 | 12 | NR | 555 | 411 | NR | 685 | 178 | NR | 815 | 3 | NR | 945 | 0 | NR |
| 430 | 21 | NR | 560 | 469 | NR | 690 | 152 | NR | 820 | 2 | NR | 950 | 0 | NR |
| 435 | 38 | NR | 565 | 536 | NR | 695 | 129 | NR | 825 | 2 | NR | 955 | 0 | NR |
| 440 | 66 | NR | 570 | 614 | NR | 700 | 109 | NR | 830 | 2 | NR | 960 | 0 | NR |
| 445 | 122 | NR | 575 | 701 | NR | 705 | 92 | NR | 835 | 1 | NR | 965 | 0 | NR |
| 450 | 215 | NR | 580 | 785 | NR | 710 | 77 | NR | 840 | 1 | NR | 970 | 0 | NR |
| 455 | 236 | NR | 585 | 863 | NR | 715 | 66 | NR | 845 | 1 | NR | 975 | 0 | NR |
| 460 | 170 | NR | 590 | 928 | NR | 720 | 55 | NR | 850 | 1 | NR | 980 | 0 | NR |
| 465 | 148 | NR | 595 | 971 | NR | 725 | 47 | NR | 855 | 1 | NR | 985 | 0 | NR |
| 470 | 132 | NR | 600 | 994 | NR | 730 | 40 | NR | 860 | 1 | NR | 990 | 0 | NR |
| 475 | 104 | NR | 605 | 996 | NR | 735 | 33 | NR | 865 | 1 | NR | 995 | 0 | NR |
| 480 | 97 | NR | 610 | 979 | NR | 740 | 28 | NR | 870 | 1 | NR | 1000 | 0 | NR |
| 485 | 105 | NR | 615 | 943 | NR | 745 | 24 | NR | 875 | 0 | NR | | | |

Summary

$R_f = 76.9$
 $R_g = 92.7$
 $CIE R_a = 70.6$
 $R_9 = -36.0$




Color Vector Graphics






Individual Sample Fidelity Index ($R_{f,i}$)

| | | | |
|------------|------------|------------|------------|
| CES01 = 87 | CES26 = 76 | CES51 = 88 | CES76 = 78 |
| CES02 = 65 | CES27 = 94 | CES52 = 85 | CES77 = 75 |
| CES03 = 32 | CES28 = 93 | CES53 = 80 | CES78 = 79 |
| CES04 = 72 | CES29 = 81 | CES54 = 86 | CES79 = 82 |
| CES05 = 51 | CES30 = 91 | CES55 = 83 | CES80 = 81 |
| CES06 = 52 | CES31 = 83 | CES56 = 77 | CES81 = 51 |
| CES07 = 44 | CES32 = 75 | CES57 = 75 | CES82 = 92 |
| CES08 = 42 | CES33 = 88 | CES58 = 76 | CES83 = 88 |
| CES09 = 29 | CES34 = 88 | CES59 = 84 | CES84 = 90 |
| CES10 = 79 | CES35 = 94 | CES60 = 91 | CES85 = 65 |
| CES11 = 62 | CES36 = 90 | CES61 = 82 | CES86 = 48 |
| CES12 = 68 | CES37 = 97 | CES62 = 91 | CES87 = 76 |
| CES13 = 45 | CES38 = 98 | CES63 = 86 | CES88 = 78 |
| CES14 = 75 | CES39 = 97 | CES64 = 70 | CES89 = 61 |
| CES15 = 72 | CES40 = 94 | CES65 = 71 | CES90 = 80 |
| CES16 = 48 | CES41 = 95 | CES66 = 71 | CES91 = 80 |
| CES17 = 51 | CES42 = 89 | CES67 = 70 | CES92 = 51 |
| CES18 = 57 | CES43 = 80 | CES68 = 74 | CES93 = 68 |
| CES19 = 74 | CES44 = 99 | CES69 = 84 | CES94 = 44 |
| CES20 = 68 | CES45 = 83 | CES70 = 72 | CES95 = 66 |
| CES21 = 88 | CES46 = 81 | CES71 = 75 | CES96 = 75 |
| CES22 = 81 | CES47 = 88 | CES72 = 89 | CES97 = 76 |
| CES23 = 92 | CES48 = 73 | CES73 = 68 | CES98 = 72 |
| CES24 = 92 | CES49 = 82 | CES74 = 85 | CES99 = 63 |
| CES25 = 73 | CES50 = 87 | CES75 = 80 | |



Color Rendition by Hue-Angle Bin



Measure Comparisons



(END OF REPORT)