Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled data based on original data using

LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: STREETWORKS

Report Number: P880071

Luminaire Tested: **MEM2-HTN-VA-40-727-U-CQ**

Issue Date: 10/01/2024

Report Generated By 670245763

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

Test Information

Test Method:	LM-79-08
Report Number:	P880071
Test Lab:	INNOVATION CENTER(G3)
Issue Date:	10/01/2024
Manufacturer:	COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line:	STREETWORKS
Catalog Number:	MEM2-HTN-VA-40-727-U-CQ
Description:	EPIC MODERN TALL HOUSING 40W 70CRI 2700K VISUAL COMFORT FIXTURE w/ TYPE V CONCENTRATED DISTRIBUTION OPTIC
Light Source:	(1) 2700K CCT, 70 CRI LEDS
Ballast/Driver:	ELECTRONIC DRIVER

Summary

Lumens per Lamp:	N/A
Luminaire Lumens:	3049.8 lumens
Efficiency:	N/A
Efficacy:	79.0 lumens/watt
Luminous Opening:	Circular (Dia: 1.12' x H: 0')
IES Classification:	Type V - Short
BUG Rating:	B1 - U0 - G1

Input Watts (W):	38.6
Input Voltage (V):	120
Input Current (Ain):	NR
Voltage Rise (V):	NR
Power Factor:	0.99
Total Harmonic Distortion (THDi):	13%
Frequency (hertz):	60
Stabilization Time:	NR
Operation Time:	NR
Ambient Temperature (°C):	NR
Test Distance:	24 FT

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P880071
CATALOG NUMBER: MEM2-HTN-VA-40-727-U-CQ

Iso-Footcandle Lines of Horizontal Illumination



Based on 15 foot mounting height. Maximum calculated value = 3.1 fc
Type V - Short - N/A

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P880071
CATALOG NUMBER: MEM2-HTN-VA-40-727-U-CQ

Luminous Intensity Polar Plot



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P880071
CATALOG NUMBER: MEM2-HTN-VA-40-727-U-CQ

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	1524.9	0.0	1524.9
	% Fixture	50.0	0.0	50.0
Street Side	Lumens	1524.9	0.0	1524.9
	% Fixture	50.0	0.0	50.0
Total	Lumens	3049.8	0.0	3049.8
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	65.7	2.2
10°-20°	193.2	6.3
20°-30°	310.8	10.2
30°-40°	419.6	13.8
40°-50°	527.6	17.3
50°-60°	593.1	19.4
60°-70°	540.1	17.7
70°-80°	326.1	10.7
80°-90°	73.5	2.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	3049.8	100.0
0°-180°	3049.8	100.0



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P880071
CATALOG NUMBER: MEM2-HTN-VA-40-727-U-CQ

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone		Lumens	% Fixture	Zone Rating/Lumen Limit B	U	G
FL	(0°-30°)	284.9	9.3			
FM	(30°-60°)	770.2	25.3			
FH	(60°-80°)	433.1	14.2			G0/660
FVH	(80°-90°)	36.8	1.2			G1/100
BL	(0°-30°)	284.9	9.3	B1/500		
BM	(30°-60°)	770.2	25.3	B1/1000		
BH	(60°-80°)	433.1	14.2	B1/500		G0/660
BVH	(80°-90°)	36.8	1.2			G1/100
UL	(90°-100°)	0.0	0.0		U0/0	
UH	(100°-180°)	0.0	0.0		U0/0	

BUG Rating: B1-U0-G1
Type V Short



Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report

REPORT NUMBER: P880071
CATALOG NUMBER: MEM2-HTN-VA-40-727-U-CQ

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
0°	689.6	689.6	689.6	689.6	689.6	689.6	689.6	689.6	689.6	689.6	689.6
2.5°	689.6	689.6	689.6	689.6	689.6	689.6	689.6	689.6	689.6	689.6	689.6
5°	688.4	688.4	688.4	688.4	688.4	688.4	688.4	688.4	688.4	688.4	689.6
7.5°	687.2	688.4	688.4	687.2	688.4	688.4	688.4	688.4	688.4	688.4	688.4
10°	686.0	686.0	687.2	687.2	687.2	687.2	687.2	687.2	687.2	687.2	686.0
12.5°	683.6	684.8	684.8	684.8	684.8	684.8	684.8	684.8	684.8	684.8	684.8
15°	682.4	682.4	682.4	682.4	682.4	682.4	682.4	682.4	681.2	681.2	682.4
17.5°	678.8	678.8	680.0	680.0	680.0	680.0	680.0	680.0	678.8	678.8	678.8
20°	676.4	676.4	677.6	677.6	677.6	678.8	677.6	676.4	676.4	676.4	676.4
22.5°	674.0	674.0	675.2	675.2	676.4	676.4	675.2	675.2	674.0	674.0	674.0
25°	671.6	671.6	671.6	672.8	674.0	672.8	672.8	671.6	670.4	669.2	669.2
27.5°	668.0	668.0	668.0	670.4	670.4	671.6	670.4	669.2	666.8	665.6	665.6
30°	664.4	664.4	665.6	668.0	669.2	669.2	668.0	665.6	663.2	662.0	662.0
32.5°	660.8	662.0	663.2	666.8	668.0	669.2	666.8	664.4	660.8	658.5	658.5
35°	660.8	660.8	664.4	668.0	671.6	672.8	670.4	665.6	660.8	657.3	657.3
37.5°	662.0	663.2	668.0	672.8	677.6	680.0	676.4	670.4	663.2	658.5	658.5
40°	666.8	666.8	672.8	681.2	687.2	688.4	684.8	676.4	666.8	660.8	659.7
42.5°	669.2	670.4	676.4	686.0	693.2	695.6	690.8	681.2	669.2	660.8	659.7
45°	669.2	670.4	677.6	688.4	698.0	700.4	695.6	683.6	670.4	662.0	659.7
47.5°	665.6	666.8	676.4	689.6	700.4	702.8	696.8	684.8	669.2	659.7	657.3
50°	660.8	662.0	671.6	688.4	701.6	706.3	699.2	683.6	665.6	654.9	652.5
52.5°	651.3	652.5	665.6	683.6	700.4	705.1	696.8	680.0	658.5	646.5	644.1
55°	636.9	639.3	652.5	674.0	693.2	699.2	689.6	670.4	647.7	633.3	630.9
57.5°	617.8	618.9	634.5	658.5	678.8	684.8	675.2	654.9	629.7	614.2	613.0
60°	590.2	592.6	610.6	634.5	656.1	662.0	652.5	630.9	604.6	587.8	586.6
62.5°	556.7	559.1	575.8	603.4	624.9	630.9	621.3	598.6	572.3	554.3	553.1
65°	514.8	517.2	533.9	560.3	583.0	589.0	580.6	556.7	530.4	513.6	511.2
67.5°	468.1	470.5	486.1	508.8	529.2	537.5	529.2	508.8	483.7	463.3	460.9
70°	411.8	411.8	427.4	450.1	469.3	480.1	469.3	448.9	423.8	407.0	407.0
72.5°	353.2	350.8	365.1	386.7	402.3	407.0	404.7	386.7	362.7	347.2	344.8
75°	282.5	287.3	298.1	313.7	330.4	337.6	329.2	313.7	296.9	283.7	282.5
77.5°	219.1	222.7	232.3	245.4	255.0	259.8	257.4	245.4	227.5	221.5	219.1
80°	154.4	156.8	165.2	174.8	182.0	186.8	183.2	173.6	164.0	158.0	155.6
82.5°	100.6	99.4	106.5	112.5	118.5	117.3	116.1	108.9	105.4	100.6	99.4
85°	51.5	52.7	52.7	58.7	59.9	62.3	61.1	58.7	52.7	50.3	51.5
87.5°	16.8	16.8	18.0	18.0	20.4	20.4	21.5	19.2	18.0	15.6	15.6
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

LM-79-2019: Approved Method: Electrical and Photometric Measurements of Solid-State Lighting Products

Report Prepared for

Cooper Lighting Solutions

Streetworks

Report Number: SP1-2407-176-2

Test Date: 09/24/2024

Luminaire Tested: MEM2-HTN-VA-30-727-U-WQ

Data in this report applies to families of products including MEM2-HTN-VA-30-727-U-WQ

Report Generated By FNC07603 / LDUCLS01DT446
Version: v7.04

Test Information

Test Method:	LM-79-2019
Report Number:	SP1-2407-176-2
Test Lab:	COOPER LIGHTING SOLUTIONS
Photometer:	SP1 - 76IN SPHERE
Measurement Geometry:	4π
Issue Date:	09/27/2024
Manufacturer:	COOPER LIGHTING SOLUTIONS
Product Line:	Streetworks
Catalog Number:	**MEM2-HTN-VA-30-727-U-WQ**
Description:	EPIC MODERN VISUAL COMFORT 30W WAVESTREAM WIDE

Spectral Parameters

CCT (K):	2691	CRI (Ra):	70.6		
CIE u':	0.2627	R1:	67.7	R9:	-27.1
CIE v':	0.5285	R2:	79.8	R10:	53.1
Duv:	0.0007	R3:	90.6	R11:	61.9
CIE x:	0.4618	R4:	67.7	R12:	42.2
CIE y:	0.4129	R5:	65.3	R13:	69.4
CIE z:	0.1254	R6:	71.1	R14:	94.1
Peak Wavelength (nm):	601	R7:	78.1	R15:	60.4
Dominant Wavelength (nm):	584	R8:	44.7		
Purity:	62.54863				

Rf:	70.6
Rg:	97.2



Test Conditions

Stabilization Time:	28M
Operation Time:	1H 28M
Sphere Temperature (°C):	25.2

REPORT NUMBER: SP1-2407-176-2

Measurement and Test Equipment			
Instrument	Identification Number	Calibration Date	Calibration Due Date
Photometer	IN0058	6/18/2024	12/18/2024
Power Meter	INXT2011004	2/8/2024	2/8/2025
AC Power Source	IN0063	10/24/2023	10/24/2024
DC Power Source	IN0208	10/24/2023	10/24/2024
Sphere Thermometer	IN0085	10/24/2023	10/24/2024
Room Thermometer	IN0046	10/24/2023	10/24/2024

REPORT NUMBER: SP1-2407-176-2

CIE 1931 Chromaticity Diagram



CIE 1931 Chromaticity Diagram with 2017 ANSI 7-Step and 4-Step Quadrangles



CCT = 2691K
CIE x = 0.4618
CIE y = 0.4129
Duv = 0.0007

Point lies inside the ANSI 2700K 4-step quadrangle

REPORT NUMBER: SP1-2407-176-2

Photopic Flux vs. Wavelength



Photopic Lumens: NR

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	43	NR	620	881	NR	750	28	NR	880	0	NR
365	0	NR	495	67	NR	625	832	NR	755	25	NR	885	0	NR
370	0	NR	500	108	NR	630	776	NR	760	22	NR	890	0	NR
375	0	NR	505	165	NR	635	720	NR	765	19	NR	895	0	NR
380	0	NR	510	229	NR	640	660	NR	770	16	NR	900	0	NR
385	0	NR	515	297	NR	645	599	NR	775	14	NR	905	0	NR
390	0	NR	520	357	NR	650	538	NR	780	12	NR	910	0	NR
395	1	NR	525	408	NR	655	480	NR	785	10	NR	915	0	NR
400	3	NR	530	451	NR	660	423	NR	790	9	NR	920	0	NR
405	5	NR	535	488	NR	665	372	NR	795	7	NR	925	0	NR
410	10	NR	540	521	NR	670	325	NR	800	6	NR	930	0	NR
415	21	NR	545	555	NR	675	282	NR	805	5	NR	935	0	NR
420	46	NR	550	590	NR	680	246	NR	810	5	NR	940	0	NR
425	94	NR	555	631	NR	685	213	NR	815	4	NR	945	0	NR
430	169	NR	560	677	NR	690	185	NR	820	4	NR	950	0	NR
435	268	NR	565	728	NR	695	158	NR	825	3	NR	955	0	NR
440	354	NR	570	782	NR	700	136	NR	830	3	NR	960	0	NR
445	445	NR	575	838	NR	705	116	NR	835	2	NR	965	0	NR
450	411	NR	580	891	NR	710	98	NR	840	2	NR	970	0	NR
455	210	NR	585	935	NR	715	82	NR	845	2	NR	975	0	NR
460	119	NR	590	972	NR	720	68	NR	850	2	NR	980	0	NR
465	84	NR	595	991	NR	725	56	NR	855	1	NR	985	0	NR
470	50	NR	600	997	NR	730	47	NR	860	1	NR	990	0	NR
475	35	NR	605	988	NR	735	40	NR	865	1	NR	995	0	NR
480	32	NR	610	965	NR	740	35	NR	870	1	NR	1000	0	NR
485	33	NR	615	927	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-176-2

Scotopic Flux vs. Wavelength



Scotopic Lumens: NR **S/P: 1.03**

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	43	NR	620	881	NR	750	28	NR	880	0	NR
365	0	NR	495	67	NR	625	832	NR	755	25	NR	885	0	NR
370	0	NR	500	108	NR	630	776	NR	760	22	NR	890	0	NR
375	0	NR	505	165	NR	635	720	NR	765	19	NR	895	0	NR
380	0	NR	510	229	NR	640	660	NR	770	16	NR	900	0	NR
385	0	NR	515	297	NR	645	599	NR	775	14	NR	905	0	NR
390	0	NR	520	357	NR	650	538	NR	780	12	NR	910	0	NR
395	1	NR	525	408	NR	655	480	NR	785	10	NR	915	0	NR
400	3	NR	530	451	NR	660	423	NR	790	9	NR	920	0	NR
405	5	NR	535	488	NR	665	372	NR	795	7	NR	925	0	NR
410	10	NR	540	521	NR	670	325	NR	800	6	NR	930	0	NR
415	21	NR	545	555	NR	675	282	NR	805	5	NR	935	0	NR
420	46	NR	550	590	NR	680	246	NR	810	5	NR	940	0	NR
425	94	NR	555	631	NR	685	213	NR	815	4	NR	945	0	NR
430	169	NR	560	677	NR	690	185	NR	820	4	NR	950	0	NR
435	268	NR	565	728	NR	695	158	NR	825	3	NR	955	0	NR
440	354	NR	570	782	NR	700	136	NR	830	3	NR	960	0	NR
445	445	NR	575	838	NR	705	116	NR	835	2	NR	965	0	NR
450	411	NR	580	891	NR	710	98	NR	840	2	NR	970	0	NR
455	210	NR	585	935	NR	715	82	NR	845	2	NR	975	0	NR
460	119	NR	590	972	NR	720	68	NR	850	2	NR	980	0	NR
465	84	NR	595	991	NR	725	56	NR	855	1	NR	985	0	NR
470	50	NR	600	997	NR	730	47	NR	860	1	NR	990	0	NR
475	35	NR	605	988	NR	735	40	NR	865	1	NR	995	0	NR
480	32	NR	610	965	NR	740	35	NR	870	1	NR	1000	0	NR
485	33	NR	615	927	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-176-2

Melanopic Flux vs. Wavelength



Melanopic Lumens: NR **M/P: 1.73**

λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)	λ (nm)	Power W^/nm	Lumens (ϕ/nm)
360	0	NR	490	43	NR	620	881	NR	750	28	NR	880	0	NR
365	0	NR	495	67	NR	625	832	NR	755	25	NR	885	0	NR
370	0	NR	500	108	NR	630	776	NR	760	22	NR	890	0	NR
375	0	NR	505	165	NR	635	720	NR	765	19	NR	895	0	NR
380	0	NR	510	229	NR	640	660	NR	770	16	NR	900	0	NR
385	0	NR	515	297	NR	645	599	NR	775	14	NR	905	0	NR
390	0	NR	520	357	NR	650	538	NR	780	12	NR	910	0	NR
395	1	NR	525	408	NR	655	480	NR	785	10	NR	915	0	NR
400	3	NR	530	451	NR	660	423	NR	790	9	NR	920	0	NR
405	5	NR	535	488	NR	665	372	NR	795	7	NR	925	0	NR
410	10	NR	540	521	NR	670	325	NR	800	6	NR	930	0	NR
415	21	NR	545	555	NR	675	282	NR	805	5	NR	935	0	NR
420	46	NR	550	590	NR	680	246	NR	810	5	NR	940	0	NR
425	94	NR	555	631	NR	685	213	NR	815	4	NR	945	0	NR
430	169	NR	560	677	NR	690	185	NR	820	4	NR	950	0	NR
435	268	NR	565	728	NR	695	158	NR	825	3	NR	955	0	NR
440	354	NR	570	782	NR	700	136	NR	830	3	NR	960	0	NR
445	445	NR	575	838	NR	705	116	NR	835	2	NR	965	0	NR
450	411	NR	580	891	NR	710	98	NR	840	2	NR	970	0	NR
455	210	NR	585	935	NR	715	82	NR	845	2	NR	975	0	NR
460	119	NR	590	972	NR	720	68	NR	850	2	NR	980	0	NR
465	84	NR	595	991	NR	725	56	NR	855	1	NR	985	0	NR
470	50	NR	600	997	NR	730	47	NR	860	1	NR	990	0	NR
475	35	NR	605	988	NR	735	40	NR	865	1	NR	995	0	NR
480	32	NR	610	965	NR	740	35	NR	870	1	NR	1000	0	NR
485	33	NR	615	927	NR	745	31	NR	875	1	NR			

REPORT NUMBER: SP1-2407-176-2

TM-30-18

Summary

R_f = 70.6
R_g = 97.2
CIE R_a = 70.6
R_9 = -27.1

Spectral Power Distribution Comparison



Color Vector Graphics









REPORT NUMBER: SP1-2407-176-2

TM-30-18

Individual Sample Fidelity Index ($R_{f,i}$)

CES01 = 86	CES26 = 57	CES51 = 79	CES76 = 50
CES02 = 63	CES27 = 80	CES52 = 81	CES77 = 76
CES03 = 31	CES28 = 81	CES53 = 68	CES78 = 56
CES04 = 71	CES29 = 49	CES54 = 80	CES79 = 83
CES05 = 50	CES30 = 56	CES55 = 78	CES80 = 81
CES06 = 52	CES31 = 55	CES56 = 66	CES81 = 71
CES07 = 42	CES32 = 52	CES57 = 64	CES82 = 92
CES08 = 41	CES33 = 58	CES58 = 67	CES83 = 85
CES09 = 29	CES34 = 69	CES59 = 84	CES84 = 89
CES10 = 77	CES35 = 84	CES60 = 91	CES85 = 81
CES11 = 60	CES36 = 88	CES61 = 84	CES86 = 62
CES12 = 66	CES37 = 78	CES62 = 78	CES87 = 77
CES13 = 44	CES38 = 64	CES63 = 69	CES88 = 75
CES14 = 74	CES39 = 92	CES64 = 67	CES89 = 65
CES15 = 72	CES40 = 86	CES65 = 64	CES90 = 71
CES16 = 48	CES41 = 80	CES66 = 61	CES91 = 96
CES17 = 51	CES42 = 79	CES67 = 59	CES92 = 64
CES18 = 57	CES43 = 67	CES68 = 67	CES93 = 78
CES19 = 73	CES44 = 98	CES69 = 77	CES94 = 51
CES20 = 67	CES45 = 77	CES70 = 59	CES95 = 72
CES21 = 88	CES46 = 72	CES71 = 56	CES96 = 77
CES22 = 80	CES47 = 67	CES72 = 85	CES97 = 79
CES23 = 92	CES48 = 57	CES73 = 50	CES98 = 72
CES24 = 92	CES49 = 69	CES74 = 94	CES99 = 63
CES25 = 73	CES50 = 79	CES75 = 58	



REPORT NUMBER: SP1-2407-176-2

TM-30-18

Color Rendition by Hue-Angle Bin







REPORT NUMBER: SP1-2407-176-2

TM-30-18

Measure Comparisons





(END OF REPORT)