

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: STREETWORKS

Report Number: P385943

Luminaire Tested: GAW-SA1C-740-U-SLL

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-2019  
Report Number: P385943  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1903-205-26)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: STREETWORKS  
Catalog Number: GAW-SA1C-740-U-SLL  
Description: GALLEON WALL LUMINAIRE  
(1) 70 CRI, 4000K, 1050mA LIGHTSQUARE WITH 16 LEDS AND SPILL LIGHT  
ELIMINATOR LEFT OPTICS  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6640 lumens  
Efficiency: N/A  
Efficacy: 112.5 lumens/watt  
Luminous Opening: Rectangular (W 0.5' x L: 0.5' x H: 0')  
IES Classification: Type III - Medium  
BUG Rating: B1 - U0 - G2

Input Watts (W): 59  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 28.75 FT




REPORT NUMBER: P385943

CATALOG NUMBER: GAW-SA1C-740-U-SLL

## Iso-Footcandle Lines of Horizontal Illumination


× Max cd  
- - - 1/2 Max cd



Based on 10 foot mounting height. Maximum calculated value = 25.4 fc  
Type III - Medium - N/A

REPORT NUMBER: P385943  
CATALOG NUMBER: GAW-SA1C-740-U-SLL

## Luminous Intensity Polar Plot



REPORT NUMBER: P385943

CATALOG NUMBER: GAW-SA1C-740-U-SLL

**FLUX DISTRIBUTION:**

|                    |           | Downward | Upward | Total  |
|--------------------|-----------|----------|--------|--------|
| <b>House Side</b>  | Lumens    | 1169.5   | 0.0    | 1169.5 |
|                    | % Fixture | 17.6     | 0.0    | 17.6   |
| <b>Street Side</b> | Lumens    | 5470.5   | 0.0    | 5470.5 |
|                    | % Fixture | 82.4     | 0.0    | 82.4   |
| <b>Total</b>       | Lumens    | 6640.0   | 0.0    | 6640.0 |
|                    | % Fixture | 100.0    | 0.0    | 100.0  |

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 156.1  | 2.4       |
| 10°-20°   | 324.3  | 4.9       |
| 20°-30°   | 461.3  | 6.9       |
| 30°-40°   | 664.7  | 10.0      |
| 40°-50°   | 936.7  | 14.1      |
| 50°-60°   | 1302.2 | 19.6      |
| 60°-70°   | 1574.8 | 23.7      |
| 70°-80°   | 968.0  | 14.6      |
| 80°-90°   | 251.9  | 3.8       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-90°    | 6640.0 | 100.0     |
| 0°-180°   | 6640.0 | 100.0     |

**Coefficient of Utilization**



REPORT NUMBER: P385943


CATALOG NUMBER: GAW-SA1C-740-U-SLL

**LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:**

| Zone |             | Lumens | % Fixture | Zone Rating/Lumen Limit |      |         |
|------|-------------|--------|-----------|-------------------------|------|---------|
|      |             |        |           | B                       | U    | G       |
| FL   | (0°-30°)    | 659.3  | 9.9       |                         |      |         |
| FM   | (30°-60°)   | 2372.8 | 35.7      |                         |      |         |
| FH   | (60°-80°)   | 2214.9 | 33.4      |                         |      | G2/5000 |
| FVH  | (80°-90°)   | 223.6  | 3.4       |                         |      | G2/225  |
| BL   | (0°-30°)    | 282.4  | 4.3       | B1/500                  |      |         |
| BM   | (30°-60°)   | 530.8  | 8.0       | B1/1000                 |      |         |
| BH   | (60°-80°)   | 327.9  | 4.9       | B1/500                  |      | G1/500  |
| BVH  | (80°-90°)   | 28.3   | 0.4       |                         |      | G1/100  |
| UL   | (90°-100°)  | 0.0    | 0.0       |                         | U0/0 |         |
| UH   | (100°-180°) | 0.0    | 0.0       |                         | U0/0 |         |

**BUG Rating: B1-U0-G2**

Type III Medium



REPORT NUMBER: P385943

CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (FULL):**

|        | 0°     | 5°     | 10°    | 15°    | 20°    | 25°    | 30°    | 35°    | 40°    | 45°    | 50°    |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 |
| 2.5°   | 2156.2 | 2184.6 | 2204.2 | 2223.6 | 2238.7 | 2253.6 | 2275.4 | 2297.1 | 2301.4 | 2305.4 | 2296.9 |
| 5°     | 2143.4 | 2212.7 | 2271.7 | 2330.3 | 2384.7 | 2439.2 | 2471.8 | 2504.5 | 2511.1 | 2517.7 | 2497.3 |
| 7.5°   | 2006.2 | 2108.4 | 2210.6 | 2312.8 | 2406.5 | 2500.2 | 2557.3 | 2614.1 | 2627.1 | 2639.9 | 2606.4 |
| 10°    | 1850.1 | 1969.0 | 2094.6 | 2220.2 | 2343.6 | 2467.0 | 2549.6 | 2632.2 | 2648.6 | 2665.1 | 2623.4 |
| 12.5°  | 1731.4 | 1861.2 | 1995.3 | 2129.4 | 2259.7 | 2389.8 | 2475.3 | 2560.8 | 2581.2 | 2601.6 | 2571.4 |
| 15°    | 1685.8 | 1828.0 | 1954.1 | 2080.2 | 2193.9 | 2307.2 | 2377.3 | 2447.1 | 2455.6 | 2463.9 | 2459.1 |
| 17.5°  | 1731.4 | 1888.3 | 2002.5 | 2116.4 | 2178.2 | 2239.8 | 2267.9 | 2295.8 | 2305.1 | 2314.1 | 2326.3 |
| 20°    | 1865.0 | 2034.3 | 2114.8 | 2194.9 | 2192.3 | 2189.4 | 2175.8 | 2162.0 | 2159.6 | 2157.2 | 2191.7 |
| 22.5°  | 2055.6 | 2252.3 | 2284.4 | 2316.3 | 2241.7 | 2167.1 | 2121.7 | 2076.0 | 2067.0 | 2057.7 | 2094.3 |
| 25°    | 2279.4 | 2488.8 | 2483.0 | 2476.9 | 2334.8 | 2192.5 | 2106.0 | 2019.5 | 2009.4 | 1999.3 | 2030.6 |
| 27.5°  | 2522.8 | 2723.0 | 2684.7 | 2646.5 | 2453.5 | 2260.5 | 2134.9 | 2009.4 | 1999.3 | 1989.2 | 2016.8 |
| 30°    | 2713.1 | 2894.7 | 2833.4 | 2772.1 | 2553.6 | 2335.1 | 2185.9 | 2036.7 | 2020.3 | 2003.5 | 2037.5 |
| 32.5°  | 2874.3 | 3028.8 | 2946.5 | 2864.2 | 2634.8 | 2405.5 | 2244.0 | 2082.6 | 2056.9 | 2031.1 | 2076.5 |
| 35°    | 3042.1 | 3162.6 | 3046.8 | 2930.8 | 2707.3 | 2483.5 | 2312.8 | 2141.8 | 2110.2 | 2078.7 | 2141.0 |
| 37.5°  | 3230.8 | 3330.9 | 3164.7 | 2998.3 | 2788.8 | 2579.3 | 2415.8 | 2252.0 | 2219.6 | 2187.2 | 2266.9 |
| 40°    | 3430.2 | 3513.5 | 3291.9 | 3070.2 | 2878.0 | 2685.8 | 2558.4 | 2430.7 | 2399.9 | 2368.8 | 2465.5 |
| 42.5°  | 3604.6 | 3665.4 | 3410.3 | 3155.2 | 2985.5 | 2815.6 | 2725.9 | 2635.9 | 2635.6 | 2635.1 | 2733.0 |
| 45°    | 3736.0 | 3788.8 | 3509.0 | 3229.0 | 3090.4 | 2951.5 | 2904.8 | 2858.1 | 2895.5 | 2932.9 | 3021.6 |
| 47.5°  | 3845.1 | 3881.0 | 3591.9 | 3302.5 | 3210.4 | 3118.3 | 3125.2 | 3132.1 | 3208.2 | 3284.4 | 3341.5 |
| 50°    | 3969.9 | 3941.0 | 3667.0 | 3392.7 | 3364.3 | 3335.9 | 3398.1 | 3459.9 | 3547.5 | 3634.9 | 3673.6 |
| 52.5°  | 4105.0 | 4028.3 | 3768.9 | 3509.3 | 3541.1 | 3573.0 | 3699.4 | 3825.7 | 3914.1 | 4002.5 | 4017.1 |
| 55°    | 4347.9 | 4230.3 | 3956.3 | 3682.1 | 3743.4 | 3804.5 | 3990.1 | 4175.4 | 4244.4 | 4313.4 | 4318.7 |
| 57.5°  | 4621.6 | 4517.3 | 4218.9 | 3920.5 | 3986.3 | 4052.2 | 4266.4 | 4480.4 | 4555.0 | 4629.3 | 4619.0 |
| 60°    | 4727.0 | 4732.1 | 4468.2 | 4204.0 | 4270.4 | 4336.8 | 4545.4 | 4754.1 | 4839.8 | 4925.3 | 4902.5 |
| 62.5°  | 4620.8 | 4745.3 | 4604.4 | 4463.1 | 4523.4 | 4583.4 | 4787.8 | 4992.2 | 5080.1 | 5168.0 | 5128.1 |
| 65°    | 4410.8 | 4534.3 | 4597.5 | 4660.7 | 4680.6 | 4700.5 | 4891.3 | 5082.0 | 5149.4 | 5216.6 | 5196.4 |
| 67.5°  | 4143.8 | 4243.6 | 4476.7 | 4709.5 | 4669.4 | 4629.3 | 4718.8 | 4808.3 | 4877.5 | 4946.8 | 4935.4 |
| 70°    | 3834.5 | 3953.4 | 4264.3 | 4575.2 | 4378.2 | 4180.9 | 4144.0 | 4107.1 | 4182.0 | 4256.6 | 4210.4 |
| 72.5°  | 3279.9 | 3459.4 | 3791.0 | 4122.3 | 3759.4 | 3396.5 | 3270.4 | 3144.3 | 3239.0 | 3333.8 | 3260.3 |
| 75°    | 2477.4 | 2715.5 | 3081.9 | 3448.0 | 3015.0 | 2582.0 | 2413.7 | 2245.4 | 2326.9 | 2408.4 | 2357.9 |
| 77.5°  | 1722.9 | 2021.6 | 2382.4 | 2743.1 | 2303.0 | 1862.6 | 1737.5 | 1612.2 | 1636.6 | 1660.8 | 1652.3 |
| 80°    | 1174.7 | 1371.2 | 1622.8 | 1874.2 | 1581.2 | 1288.1 | 1297.9 | 1307.5 | 1296.0 | 1284.4 | 1301.4 |
| 82.5°  | 736.7  | 875.0  | 1069.3 | 1263.4 | 1107.8 | 952.3  | 1041.5 | 1130.7 | 1086.8 | 1042.8 | 1059.2 |
| 85°    | 414.9  | 499.4  | 689.4  | 879.2  | 819.5  | 759.5  | 811.8  | 863.9  | 795.9  | 727.9  | 757.9  |
| 87.5°  | 79.1   | 131.7  | 381.5  | 631.0  | 572.9  | 514.8  | 447.3  | 379.9  | 289.9  | 199.9  | 292.0  |
| 90°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 92.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 95°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 97.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 100°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 102.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 105°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 107.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 110°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |



REPORT NUMBER: P385943  
 CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 0°  | 5°  | 10° | 15° | 20° | 25° | 30° | 35° | 40° | 45° | 50° |
|--------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 112.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 115°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 117.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 120°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 122.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 125°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 127.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 130°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 132.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 135°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 137.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 140°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 142.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 145°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 147.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 150°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 152.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 155°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 157.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 160°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 162.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 165°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 167.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 170°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 172.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 175°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 177.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |
| 180°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 |



REPORT NUMBER: P385943

CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 55°    | 60°    | 65°    | 70°    | 75°    | 80°    | 85°    | 90°    | 95°    | 100°   | 105°   |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 |
| 2.5°   | 2288.4 | 2283.9 | 2279.4 | 2263.2 | 2246.7 | 2222.3 | 2202.1 | 2167.1 | 2147.9 | 2119.0 | 2090.1 |
| 5°     | 2476.6 | 2447.9 | 2419.3 | 2369.9 | 2320.2 | 2265.0 | 2201.6 | 2131.2 | 2078.1 | 2009.1 | 1940.1 |
| 7.5°   | 2573.0 | 2506.1 | 2438.9 | 2344.1 | 2249.1 | 2163.6 | 2063.3 | 1969.8 | 1890.2 | 1800.4 | 1710.7 |
| 10°    | 2581.7 | 2481.4 | 2380.8 | 2257.6 | 2134.1 | 2030.3 | 1914.9 | 1811.1 | 1715.5 | 1612.5 | 1509.2 |
| 12.5°  | 2540.8 | 2434.1 | 2327.1 | 2191.5 | 2055.6 | 1937.7 | 1813.4 | 1697.2 | 1591.2 | 1477.9 | 1364.3 |
| 15°    | 2454.3 | 2369.1 | 2283.6 | 2156.4 | 2029.3 | 1910.3 | 1789.8 | 1652.0 | 1532.3 | 1416.3 | 1300.0 |
| 17.5°  | 2338.3 | 2297.9 | 2257.3 | 2165.5 | 2073.3 | 1970.3 | 1853.5 | 1691.9 | 1551.7 | 1425.6 | 1299.5 |
| 20°    | 2226.0 | 2240.9 | 2255.5 | 2218.8 | 2182.2 | 2099.6 | 1997.7 | 1816.1 | 1637.2 | 1472.3 | 1307.2 |
| 22.5°  | 2130.7 | 2202.1 | 2273.2 | 2301.7 | 2329.8 | 2280.2 | 2200.5 | 1990.5 | 1753.7 | 1538.4 | 1323.1 |
| 25°    | 2061.7 | 2180.1 | 2298.5 | 2393.0 | 2487.2 | 2465.2 | 2403.9 | 2202.4 | 1908.2 | 1633.7 | 1359.0 |
| 27.5°  | 2044.4 | 2189.6 | 2334.8 | 2481.4 | 2627.7 | 2648.1 | 2631.1 | 2425.6 | 2092.5 | 1752.1 | 1411.5 |
| 30°    | 2071.5 | 2218.6 | 2365.4 | 2543.8 | 2721.9 | 2803.4 | 2826.2 | 2611.7 | 2303.0 | 1890.2 | 1477.1 |
| 32.5°  | 2121.9 | 2266.1 | 2410.2 | 2604.6 | 2798.6 | 2921.8 | 2994.5 | 2781.9 | 2449.8 | 1994.2 | 1538.4 |
| 35°    | 2203.4 | 2338.3 | 2473.1 | 2675.4 | 2877.7 | 3037.0 | 3169.8 | 2957.6 | 2580.1 | 2067.0 | 1553.6 |
| 37.5°  | 2346.3 | 2462.3 | 2578.3 | 2765.2 | 2951.8 | 3158.3 | 3357.7 | 3151.2 | 2721.1 | 2137.1 | 1552.8 |
| 40°    | 2562.1 | 2644.1 | 2725.9 | 2883.8 | 3041.5 | 3301.4 | 3570.6 | 3367.0 | 2876.9 | 2213.0 | 1549.0 |
| 42.5°  | 2831.0 | 2873.2 | 2915.2 | 3040.2 | 3165.2 | 3450.9 | 3763.9 | 3578.1 | 3025.6 | 2283.6 | 1541.6 |
| 45°    | 3110.0 | 3121.2 | 3132.3 | 3211.2 | 3289.7 | 3569.3 | 3895.6 | 3736.5 | 3155.4 | 2344.9 | 1534.2 |
| 47.5°  | 3398.3 | 3360.1 | 3321.9 | 3353.2 | 3384.5 | 3660.1 | 3989.5 | 3856.8 | 3285.8 | 2412.9 | 1539.7 |
| 50°    | 3712.4 | 3605.9 | 3499.5 | 3483.0 | 3466.6 | 3750.9 | 4100.2 | 4009.7 | 3442.4 | 2511.9 | 1581.4 |
| 52.5°  | 4031.5 | 3856.0 | 3680.5 | 3615.5 | 3550.2 | 3859.2 | 4247.0 | 4200.1 | 3665.9 | 2665.4 | 1664.5 |
| 55°    | 4324.0 | 4100.8 | 3877.5 | 3789.9 | 3702.3 | 4024.8 | 4426.2 | 4479.6 | 3952.4 | 2861.5 | 1770.4 |
| 57.5°  | 4608.4 | 4355.4 | 4102.4 | 4021.1 | 3939.9 | 4268.3 | 4653.2 | 4730.5 | 4241.7 | 3049.8 | 1857.5 |
| 60°    | 4879.7 | 4629.3 | 4378.7 | 4313.7 | 4248.4 | 4570.9 | 4898.5 | 4842.2 | 4390.9 | 3137.9 | 1884.6 |
| 62.5°  | 5088.3 | 4889.2 | 4690.1 | 4655.9 | 4621.4 | 4877.0 | 5087.0 | 4798.7 | 4296.2 | 3051.1 | 1806.0 |
| 65°    | 5176.2 | 5062.8 | 4949.2 | 4981.3 | 5013.2 | 5108.5 | 5134.0 | 4671.3 | 3998.3 | 2807.9 | 1617.5 |
| 67.5°  | 4923.7 | 4946.8 | 4969.9 | 5104.8 | 5239.4 | 5173.8 | 4994.4 | 4420.1 | 3574.3 | 2463.3 | 1352.3 |
| 70°    | 4163.9 | 4302.5 | 4440.8 | 4759.9 | 5078.8 | 4933.3 | 4620.3 | 3969.4 | 3064.1 | 2066.4 | 1068.5 |
| 72.5°  | 3186.5 | 3342.3 | 3497.9 | 3971.5 | 4444.8 | 4310.8 | 3927.4 | 3260.3 | 2456.7 | 1650.2 | 843.4  |
| 75°    | 2307.2 | 2483.2 | 2659.0 | 3181.4 | 3703.9 | 3517.8 | 2937.7 | 2334.3 | 1866.0 | 1259.7 | 653.1  |
| 77.5°  | 1643.5 | 1761.4 | 1879.3 | 2395.4 | 2911.2 | 2608.0 | 1955.5 | 1570.8 | 1291.5 | 875.5  | 459.3  |
| 80°    | 1318.3 | 1282.2 | 1246.1 | 1533.6 | 1821.1 | 1770.7 | 1293.4 | 1008.8 | 893.8  | 586.7  | 279.5  |
| 82.5°  | 1075.4 | 987.3  | 899.2  | 1034.5 | 1169.9 | 1162.5 | 897.6  | 740.1  | 665.3  | 407.8  | 150.3  |
| 85°    | 787.7  | 752.4  | 717.0  | 836.8  | 956.5  | 854.3  | 607.9  | 470.4  | 518.7  | 300.3  | 81.8   |
| 87.5°  | 384.1  | 438.8  | 493.2  | 634.5  | 775.4  | 582.2  | 184.5  | 91.3   | 126.4  | 83.1   | 39.6   |
| 90°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 92.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 95°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 97.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 100°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 102.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 105°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 107.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 110°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |



REPORT NUMBER: P385943  
 CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 55° | 60° | 65° | 70° | 75° | 80° | 85° | 90° | 95° | 100° | 105° |
|--------|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|
| 112.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 115°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 117.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 120°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 122.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 125°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 127.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 130°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 132.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 135°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 137.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 140°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 142.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 145°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 147.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 150°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 152.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 155°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 157.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 160°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 162.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 165°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 167.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 170°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 172.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 175°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 177.5° | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |
| 180°   | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0  | 0.0  |



REPORT NUMBER: P385943

CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 110°   | 115°   | 120°   | 125°   | 130°   | 135°   | 140°   | 145°   | 150°   | 155°   | 160°   |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 |
| 2.5°   | 2068.6 | 2046.8 | 2022.1 | 1997.4 | 1969.3 | 1940.9 | 1924.2 | 1907.2 | 1888.8 | 1870.5 | 1849.8 |
| 5°     | 1894.4 | 1848.8 | 1797.0 | 1745.2 | 1694.0 | 1642.7 | 1615.1 | 1587.5 | 1558.3 | 1528.9 | 1503.4 |
| 7.5°   | 1644.3 | 1577.7 | 1506.0 | 1434.1 | 1370.4 | 1306.4 | 1266.8 | 1227.0 | 1190.9 | 1154.5 | 1124.0 |
| 10°    | 1424.3 | 1339.3 | 1267.4 | 1195.2 | 1147.1 | 1099.1 | 1062.7 | 1026.3 | 991.3  | 956.0  | 922.3  |
| 12.5°  | 1279.3 | 1194.4 | 1148.7 | 1103.0 | 1063.2 | 1023.4 | 981.5  | 939.2  | 891.2  | 842.9  | 807.6  |
| 15°    | 1222.8 | 1145.5 | 1094.8 | 1043.8 | 990.5  | 936.9  | 885.4  | 833.9  | 777.0  | 720.2  | 680.1  |
| 17.5°  | 1198.3 | 1097.2 | 1026.3 | 955.2  | 884.8  | 814.5  | 754.7  | 695.0  | 632.9  | 570.8  | 530.2  |
| 20°    | 1172.6 | 1038.0 | 943.0  | 847.7  | 757.4  | 667.1  | 599.4  | 531.7  | 476.3  | 420.8  | 389.7  |
| 22.5°  | 1149.2 | 975.1  | 855.9  | 736.4  | 629.7  | 523.0  | 456.6  | 390.0  | 356.0  | 322.0  | 309.5  |
| 25°    | 1139.7 | 920.1  | 773.6  | 627.0  | 514.5  | 401.7  | 354.4  | 307.2  | 294.1  | 280.9  | 274.5  |
| 27.5°  | 1141.3 | 871.0  | 704.3  | 537.3  | 435.9  | 334.5  | 302.1  | 269.7  | 261.8  | 253.5  | 249.5  |
| 30°    | 1147.4 | 817.7  | 639.0  | 460.3  | 376.7  | 293.1  | 272.1  | 250.9  | 242.4  | 233.9  | 228.8  |
| 32.5°  | 1154.3 | 769.9  | 588.6  | 407.0  | 338.7  | 270.3  | 253.0  | 235.5  | 227.2  | 219.0  | 214.0  |
| 35°    | 1142.3 | 730.8  | 554.0  | 377.2  | 314.3  | 251.1  | 236.5  | 221.7  | 212.6  | 203.6  | 198.8  |
| 37.5°  | 1122.2 | 691.6  | 527.2  | 362.6  | 298.4  | 233.9  | 223.3  | 212.4  | 203.1  | 193.5  | 189.0  |
| 40°    | 1103.8 | 658.4  | 507.3  | 356.0  | 289.6  | 223.0  | 214.0  | 204.9  | 195.4  | 185.6  | 180.3  |
| 42.5°  | 1089.0 | 636.1  | 487.7  | 339.3  | 281.7  | 223.8  | 211.1  | 198.0  | 188.8  | 179.5  | 173.6  |
| 45°    | 1077.8 | 621.5  | 472.3  | 323.1  | 274.2  | 225.4  | 209.2  | 193.0  | 183.7  | 174.2  | 167.2  |
| 47.5°  | 1076.8 | 613.8  | 461.4  | 309.0  | 260.2  | 211.1  | 204.4  | 197.8  | 184.2  | 170.4  | 162.5  |
| 50°    | 1091.4 | 601.3  | 448.7  | 295.7  | 246.6  | 197.5  | 206.5  | 215.3  | 192.2  | 168.8  | 158.8  |
| 52.5°  | 1121.9 | 579.3  | 428.5  | 277.7  | 230.2  | 182.4  | 196.5  | 210.3  | 190.3  | 170.2  | 157.2  |
| 55°    | 1158.8 | 546.9  | 397.9  | 248.7  | 208.4  | 167.8  | 180.3  | 192.5  | 180.0  | 167.2  | 151.6  |
| 57.5°  | 1181.9 | 506.0  | 359.5  | 212.9  | 184.0  | 155.0  | 162.2  | 169.1  | 164.1  | 159.0  | 143.1  |
| 60°    | 1168.1 | 451.6  | 316.2  | 180.5  | 162.5  | 144.4  | 143.1  | 141.5  | 148.9  | 156.4  | 138.0  |
| 62.5°  | 1100.7 | 395.3  | 278.0  | 160.6  | 147.1  | 133.3  | 130.3  | 127.2  | 139.4  | 151.3  | 131.9  |
| 65°    | 986.8  | 356.0  | 253.8  | 151.6  | 136.5  | 121.3  | 118.1  | 114.9  | 118.7  | 122.4  | 113.4  |
| 67.5°  | 842.1  | 331.8  | 240.0  | 148.1  | 129.8  | 111.2  | 107.5  | 103.8  | 103.0  | 102.2  | 99.0   |
| 70°    | 692.9  | 317.0  | 231.0  | 144.9  | 122.6  | 100.1  | 96.6   | 93.2   | 92.1   | 90.8   | 88.4   |
| 72.5°  | 579.3  | 315.1  | 229.9  | 144.7  | 116.8  | 88.9   | 85.7   | 82.6   | 81.2   | 79.6   | 77.8   |
| 75°    | 474.4  | 295.7  | 218.2  | 140.7  | 108.8  | 76.7   | 73.8   | 70.9   | 69.8   | 68.5   | 66.9   |
| 77.5°  | 352.0  | 244.8  | 183.4  | 122.1  | 93.2   | 64.2   | 61.3   | 58.1   | 57.9   | 57.3   | 56.0   |
| 80°    | 228.3  | 177.1  | 131.1  | 85.2   | 68.0   | 50.4   | 48.1   | 45.4   | 45.7   | 45.9   | 44.9   |
| 82.5°  | 126.9  | 103.3  | 80.2   | 57.1   | 46.5   | 35.8   | 34.8   | 33.4   | 34.2   | 34.8   | 33.4   |
| 85°    | 66.9   | 52.0   | 43.0   | 34.0   | 26.8   | 19.6   | 19.6   | 19.4   | 20.4   | 21.5   | 20.4   |
| 87.5°  | 28.9   | 18.3   | 15.7   | 12.7   | 7.2    | 1.3    | 1.6    | 1.6    | 2.1    | 2.7    | 2.4    |
| 90°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 92.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 95°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 97.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 100°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 102.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 105°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 107.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 110°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |



REPORT NUMBER: P385943  
 CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 110° | 115° | 120° | 125° | 130° | 135° | 140° | 145° | 150° | 155° | 160° |
|--------|------|------|------|------|------|------|------|------|------|------|------|
| 112.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 115°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 117.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 120°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 122.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 125°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 127.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 130°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 132.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 135°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 137.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 140°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 142.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 145°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 147.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 150°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 152.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 155°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 157.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 160°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 162.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 165°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 167.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 170°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 172.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 175°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 177.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 180°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |



REPORT NUMBER: P385943

CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 165°   | 170°   | 175°   | 180°   | 185°   | 190°   | 195°   | 200°   | 205°   | 210°   | 215°   |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 |
| 2.5°   | 1828.8 | 1809.5 | 1789.8 | 1768.3 | 1772.3 | 1755.8 | 1739.4 | 1729.0 | 1718.7 | 1715.5 | 1712.3 |
| 5°     | 1477.9 | 1455.9 | 1433.6 | 1413.6 | 1430.9 | 1419.2 | 1407.5 | 1405.9 | 1404.1 | 1404.1 | 1403.8 |
| 7.5°   | 1093.5 | 1069.9 | 1046.0 | 1029.5 | 1046.5 | 1044.4 | 1042.2 | 1053.7 | 1065.1 | 1074.4 | 1083.4 |
| 10°    | 888.5  | 859.9  | 830.9  | 806.5  | 802.3  | 790.0  | 777.6  | 780.2  | 782.6  | 792.7  | 802.8  |
| 12.5°  | 772.3  | 738.0  | 703.8  | 675.1  | 662.1  | 641.9  | 621.5  | 608.7  | 596.0  | 597.3  | 598.4  |
| 15°    | 639.8  | 606.6  | 573.2  | 548.5  | 540.2  | 524.6  | 508.9  | 493.0  | 476.8  | 470.2  | 463.3  |
| 17.5°  | 489.3  | 462.7  | 435.9  | 419.4  | 419.4  | 414.9  | 410.4  | 402.5  | 394.2  | 387.6  | 380.7  |
| 20°    | 358.7  | 344.6  | 330.2  | 323.3  | 325.5  | 325.7  | 325.7  | 329.7  | 333.7  | 331.6  | 329.5  |
| 22.5°  | 296.8  | 291.8  | 286.7  | 283.8  | 284.9  | 285.1  | 285.4  | 289.1  | 292.6  | 295.2  | 297.6  |
| 25°    | 267.9  | 264.7  | 261.5  | 260.4  | 262.8  | 263.1  | 263.1  | 265.5  | 267.9  | 270.5  | 273.2  |
| 27.5°  | 245.3  | 244.0  | 242.6  | 240.8  | 243.2  | 243.2  | 242.9  | 245.6  | 248.0  | 250.3  | 252.5  |
| 30°    | 223.8  | 224.3  | 224.6  | 224.1  | 225.7  | 226.7  | 227.5  | 229.4  | 231.0  | 232.8  | 234.7  |
| 32.5°  | 208.7  | 207.9  | 207.1  | 206.5  | 210.0  | 211.8  | 213.7  | 215.6  | 217.2  | 218.0  | 218.8  |
| 35°    | 194.1  | 192.2  | 190.3  | 189.0  | 192.2  | 194.6  | 197.0  | 200.4  | 203.6  | 204.1  | 204.7  |
| 37.5°  | 184.2  | 181.8  | 179.5  | 177.9  | 179.2  | 180.3  | 181.3  | 185.0  | 188.8  | 190.9  | 192.7  |
| 40°    | 174.9  | 172.6  | 170.2  | 168.8  | 169.6  | 169.9  | 170.2  | 172.0  | 173.6  | 177.6  | 181.3  |
| 42.5°  | 167.5  | 164.6  | 161.7  | 160.1  | 160.6  | 161.1  | 161.4  | 161.1  | 160.9  | 164.6  | 168.3  |
| 45°    | 160.1  | 156.9  | 153.7  | 151.9  | 152.1  | 152.1  | 152.1  | 151.6  | 150.8  | 152.6  | 154.5  |
| 47.5°  | 154.2  | 150.5  | 146.8  | 144.9  | 144.4  | 143.9  | 143.4  | 143.1  | 142.6  | 143.9  | 144.9  |
| 50°    | 148.4  | 144.4  | 140.2  | 138.0  | 136.7  | 136.2  | 135.7  | 135.4  | 134.9  | 136.2  | 137.2  |
| 52.5°  | 143.9  | 139.1  | 134.3  | 130.9  | 129.6  | 128.8  | 128.0  | 128.2  | 128.2  | 128.8  | 129.0  |
| 55°    | 135.9  | 131.7  | 127.2  | 124.8  | 122.4  | 121.9  | 121.3  | 122.1  | 122.6  | 122.6  | 122.6  |
| 57.5°  | 127.2  | 123.2  | 118.9  | 117.3  | 115.2  | 115.2  | 114.9  | 116.0  | 116.8  | 117.3  | 117.9  |
| 60°    | 119.5  | 114.9  | 110.4  | 109.1  | 108.3  | 108.0  | 107.8  | 109.1  | 110.2  | 111.2  | 112.3  |
| 62.5°  | 112.3  | 107.5  | 102.7  | 101.1  | 100.9  | 101.1  | 101.1  | 102.5  | 103.5  | 104.6  | 105.7  |
| 65°    | 104.3  | 99.6   | 94.5   | 92.9   | 93.4   | 94.2   | 95.0   | 96.1   | 96.9   | 98.0   | 99.0   |
| 67.5°  | 95.6   | 91.6   | 87.3   | 85.7   | 86.0   | 87.1   | 88.1   | 88.9   | 89.5   | 90.5   | 91.6   |
| 70°    | 86.0   | 82.6   | 79.1   | 78.0   | 77.8   | 79.1   | 80.2   | 80.7   | 81.2   | 82.6   | 83.6   |
| 72.5°  | 75.7   | 72.7   | 69.8   | 69.0   | 69.3   | 70.1   | 70.9   | 71.7   | 72.2   | 73.5   | 74.6   |
| 75°    | 65.0   | 62.4   | 59.7   | 59.2   | 59.7   | 60.5   | 61.3   | 61.9   | 62.4   | 64.0   | 65.3   |
| 77.5°  | 54.7   | 51.8   | 48.6   | 48.3   | 49.1   | 49.9   | 50.4   | 51.2   | 52.0   | 54.2   | 56.3   |
| 80°    | 43.8   | 40.6   | 37.2   | 36.9   | 37.7   | 38.5   | 39.3   | 40.1   | 40.9   | 43.5   | 45.9   |
| 82.5°  | 32.1   | 28.4   | 24.7   | 24.2   | 26.8   | 27.6   | 28.4   | 29.7   | 30.8   | 33.2   | 35.6   |
| 85°    | 19.4   | 15.7   | 11.9   | 11.7   | 14.1   | 15.4   | 16.7   | 18.3   | 19.6   | 21.8   | 23.9   |
| 87.5°  | 2.1    | 1.1    | 0.0    | 0.0    | 0.3    | 1.3    | 2.4    | 3.7    | 5.0    | 7.2    | 9.0    |
| 90°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 92.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 95°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 97.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 100°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 102.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 105°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 107.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 110°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |



REPORT NUMBER: P385943  
 CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 165° | 170° | 175° | 180° | 185° | 190° | 195° | 200° | 205° | 210° | 215° |
|--------|------|------|------|------|------|------|------|------|------|------|------|
| 112.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 115°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 117.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 120°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 122.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 125°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 127.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 130°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 132.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 135°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 137.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 140°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 142.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 145°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 147.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 150°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 152.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 155°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 157.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 160°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 162.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 165°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 167.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 170°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 172.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 175°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 177.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 180°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |



REPORT NUMBER: P385943

CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 220°   | 225°   | 230°   | 235°   | 240°   | 245°   | 250°   | 255°   | 260°   | 265°   | 270°   |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 |
| 2.5°   | 1700.6 | 1688.7 | 1700.9 | 1712.8 | 1717.9 | 1722.9 | 1709.9 | 1696.6 | 1717.3 | 1737.8 | 1743.1 |
| 5°     | 1393.2 | 1382.3 | 1390.5 | 1398.5 | 1380.7 | 1362.9 | 1361.1 | 1359.0 | 1374.4 | 1389.8 | 1392.1 |
| 7.5°   | 1079.9 | 1076.5 | 1084.2 | 1091.9 | 1069.3 | 1046.5 | 1035.3 | 1024.2 | 1027.9 | 1031.6 | 1031.1 |
| 10°    | 805.2  | 807.3  | 816.9  | 826.2  | 808.6  | 791.1  | 783.4  | 775.7  | 784.2  | 792.4  | 800.1  |
| 12.5°  | 603.2  | 607.7  | 617.8  | 627.6  | 620.4  | 613.0  | 613.8  | 614.6  | 624.4  | 634.0  | 642.4  |
| 15°    | 468.6  | 473.9  | 481.0  | 487.9  | 488.2  | 488.2  | 495.1  | 501.7  | 500.9  | 500.2  | 506.0  |
| 17.5°  | 387.9  | 394.8  | 395.6  | 396.4  | 396.6  | 396.9  | 396.4  | 395.8  | 391.8  | 387.9  | 392.4  |
| 20°    | 332.1  | 334.5  | 336.6  | 338.5  | 336.1  | 333.4  | 326.8  | 320.2  | 317.5  | 314.9  | 319.1  |
| 22.5°  | 302.1  | 306.4  | 304.2  | 301.8  | 297.1  | 292.0  | 287.0  | 281.7  | 281.4  | 280.9  | 283.3  |
| 25°    | 276.9  | 280.3  | 276.6  | 272.9  | 269.5  | 266.0  | 262.6  | 259.1  | 258.8  | 258.6  | 259.6  |
| 27.5°  | 255.9  | 259.1  | 255.7  | 252.2  | 249.3  | 246.4  | 243.7  | 241.0  | 240.5  | 240.0  | 240.3  |
| 30°    | 237.9  | 240.8  | 237.9  | 234.7  | 232.6  | 230.2  | 228.3  | 226.4  | 226.2  | 225.9  | 225.9  |
| 32.5°  | 221.7  | 224.6  | 222.5  | 220.3  | 218.5  | 216.6  | 215.3  | 214.0  | 212.6  | 211.3  | 208.4  |
| 35°    | 207.6  | 210.5  | 209.2  | 207.6  | 205.5  | 203.4  | 201.0  | 198.3  | 194.9  | 191.1  | 189.5  |
| 37.5°  | 195.7  | 198.6  | 197.2  | 195.9  | 193.0  | 190.1  | 185.8  | 181.3  | 180.3  | 178.9  | 178.7  |
| 40°    | 186.1  | 190.6  | 188.0  | 185.0  | 180.5  | 176.0  | 173.9  | 171.8  | 171.2  | 170.7  | 170.2  |
| 42.5°  | 175.5  | 182.4  | 177.6  | 172.8  | 168.6  | 164.3  | 163.8  | 163.3  | 163.0  | 162.7  | 162.7  |
| 45°    | 162.2  | 169.6  | 164.9  | 159.8  | 157.4  | 155.0  | 155.0  | 155.0  | 155.3  | 155.3  | 155.8  |
| 47.5°  | 149.7  | 154.2  | 151.9  | 149.5  | 148.1  | 146.8  | 147.1  | 147.3  | 148.1  | 148.7  | 150.0  |
| 50°    | 139.1  | 140.7  | 141.2  | 141.5  | 140.7  | 139.9  | 140.4  | 140.7  | 141.5  | 142.0  | 143.1  |
| 52.5°  | 131.4  | 133.8  | 133.8  | 133.5  | 133.5  | 133.5  | 134.1  | 134.6  | 135.4  | 136.2  | 137.2  |
| 55°    | 126.4  | 129.8  | 128.8  | 127.7  | 128.0  | 128.0  | 128.5  | 129.0  | 129.8  | 130.3  | 131.9  |
| 57.5°  | 121.6  | 125.3  | 124.2  | 123.2  | 123.2  | 123.2  | 123.4  | 123.7  | 124.5  | 125.0  | 126.1  |
| 60°    | 116.0  | 119.7  | 118.7  | 117.3  | 117.6  | 117.9  | 118.1  | 118.1  | 118.7  | 118.9  | 118.9  |
| 62.5°  | 109.4  | 113.1  | 112.0  | 110.7  | 111.5  | 112.0  | 112.0  | 112.0  | 112.6  | 112.8  | 112.0  |
| 65°    | 102.5  | 105.9  | 104.9  | 103.8  | 104.9  | 105.7  | 106.2  | 106.5  | 106.2  | 105.9  | 105.1  |
| 67.5°  | 95.0   | 98.5   | 97.4   | 96.1   | 97.4   | 98.5   | 99.6   | 100.3  | 99.6   | 98.8   | 97.7   |
| 70°    | 87.1   | 90.5   | 89.2   | 87.9   | 89.2   | 90.5   | 91.6   | 92.7   | 91.6   | 90.5   | 90.3   |
| 72.5°  | 78.6   | 82.6   | 81.0   | 79.4   | 81.0   | 82.6   | 83.1   | 83.6   | 82.8   | 82.0   | 81.5   |
| 75°    | 69.3   | 73.3   | 71.9   | 70.4   | 71.7   | 73.0   | 73.3   | 73.5   | 73.5   | 73.3   | 71.7   |
| 77.5°  | 59.5   | 62.7   | 61.9   | 61.1   | 61.9   | 62.7   | 62.7   | 62.7   | 62.9   | 62.9   | 60.8   |
| 80°    | 47.8   | 49.6   | 49.9   | 50.2   | 50.4   | 50.7   | 50.4   | 50.2   | 49.6   | 49.1   | 47.8   |
| 82.5°  | 35.6   | 35.6   | 37.7   | 39.6   | 39.6   | 39.3   | 39.0   | 38.5   | 37.4   | 36.1   | 33.2   |
| 85°    | 22.6   | 21.2   | 24.7   | 27.9   | 27.9   | 27.6   | 27.1   | 26.3   | 24.2   | 21.8   | 19.4   |
| 87.5°  | 7.7    | 6.4    | 9.8    | 13.3   | 13.5   | 13.5   | 13.0   | 12.5   | 10.4   | 8.0    | 6.1    |
| 90°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 92.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 95°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 97.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 100°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 102.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 105°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 107.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 110°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |



REPORT NUMBER: P385943  
 CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 220° | 225° | 230° | 235° | 240° | 245° | 250° | 255° | 260° | 265° | 270° |
|--------|------|------|------|------|------|------|------|------|------|------|------|
| 112.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 115°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 117.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 120°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 122.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 125°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 127.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 130°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 132.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 135°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 137.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 140°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 142.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 145°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 147.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 150°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 152.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 155°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 157.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 160°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 162.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 165°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 167.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 170°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 172.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 175°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 177.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 180°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |



REPORT NUMBER: P385943

CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 275°   | 280°   | 285°   | 290°   | 295°   | 300°   | 305°   | 310°   | 315°   | 320°   | 325°   |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 |
| 2.5°   | 1751.1 | 1754.5 | 1757.7 | 1783.7 | 1809.5 | 1839.7 | 1870.0 | 1893.1 | 1915.9 | 1939.5 | 1963.2 |
| 5°     | 1400.4 | 1404.6 | 1408.9 | 1440.5 | 1471.8 | 1514.0 | 1556.2 | 1592.6 | 1628.9 | 1671.7 | 1714.4 |
| 7.5°   | 1038.0 | 1047.3 | 1056.3 | 1090.0 | 1123.5 | 1168.9 | 1214.0 | 1261.5 | 1308.8 | 1364.5 | 1420.3 |
| 10°    | 815.3  | 832.8  | 850.0  | 884.6  | 919.1  | 963.9  | 1008.5 | 1058.2 | 1107.8 | 1162.8 | 1217.5 |
| 12.5°  | 660.0  | 683.3  | 706.4  | 747.8  | 789.3  | 842.9  | 896.2  | 951.5  | 1006.4 | 1054.7 | 1103.0 |
| 15°    | 521.4  | 546.9  | 572.1  | 615.9  | 659.7  | 718.6  | 777.3  | 837.6  | 897.6  | 955.4  | 1013.3 |
| 17.5°  | 406.7  | 427.7  | 448.4  | 485.6  | 522.5  | 579.5  | 636.6  | 699.8  | 763.0  | 833.6  | 903.9  |
| 20°    | 328.1  | 336.9  | 345.6  | 372.5  | 399.0  | 445.5  | 491.7  | 556.2  | 620.7  | 705.1  | 789.5  |
| 22.5°  | 287.5  | 292.0  | 296.3  | 309.3  | 322.0  | 352.0  | 381.8  | 438.8  | 495.6  | 587.8  | 679.6  |
| 25°    | 263.1  | 266.5  | 270.0  | 278.5  | 287.0  | 301.3  | 315.6  | 355.7  | 395.8  | 486.3  | 576.6  |
| 27.5°  | 241.0  | 246.4  | 251.4  | 255.4  | 259.1  | 268.9  | 278.5  | 304.8  | 331.0  | 415.5  | 499.6  |
| 30°    | 225.1  | 227.0  | 228.8  | 234.9  | 240.8  | 250.9  | 261.0  | 279.3  | 297.6  | 369.0  | 440.2  |
| 32.5°  | 206.5  | 209.2  | 211.8  | 218.2  | 224.6  | 233.9  | 243.2  | 258.0  | 272.6  | 333.7  | 394.5  |
| 35°    | 189.8  | 192.5  | 195.1  | 201.5  | 207.6  | 217.7  | 227.5  | 240.0  | 252.2  | 305.3  | 358.4  |
| 37.5°  | 179.5  | 182.1  | 184.8  | 190.3  | 195.7  | 205.7  | 215.6  | 225.4  | 234.9  | 284.1  | 333.2  |
| 40°    | 170.7  | 173.4  | 176.0  | 181.3  | 186.4  | 196.2  | 205.7  | 214.0  | 222.2  | 268.1  | 314.1  |
| 42.5°  | 163.0  | 165.9  | 168.8  | 174.2  | 179.2  | 188.0  | 196.7  | 207.6  | 218.2  | 254.3  | 290.2  |
| 45°    | 156.6  | 159.5  | 162.2  | 168.0  | 173.9  | 182.4  | 190.9  | 206.0  | 221.1  | 247.2  | 273.2  |
| 47.5°  | 150.8  | 154.0  | 156.9  | 163.3  | 169.6  | 180.3  | 190.6  | 203.4  | 215.8  | 241.6  | 267.3  |
| 50°    | 145.2  | 148.9  | 152.6  | 160.3  | 167.8  | 185.6  | 203.1  | 204.9  | 206.5  | 237.1  | 267.3  |
| 52.5°  | 139.9  | 144.2  | 148.4  | 158.0  | 167.2  | 188.0  | 208.7  | 202.0  | 195.1  | 228.6  | 262.0  |
| 55°    | 134.6  | 138.3  | 141.8  | 153.4  | 165.1  | 180.3  | 195.4  | 186.6  | 177.6  | 212.6  | 247.7  |
| 57.5°  | 127.4  | 131.4  | 135.1  | 147.6  | 160.1  | 170.7  | 181.1  | 173.1  | 164.9  | 194.6  | 224.1  |
| 60°    | 120.0  | 124.5  | 129.0  | 144.9  | 160.6  | 158.8  | 156.6  | 155.0  | 153.2  | 174.4  | 195.7  |
| 62.5°  | 113.4  | 118.1  | 122.9  | 143.6  | 164.3  | 151.6  | 138.8  | 140.2  | 141.2  | 156.9  | 172.6  |
| 65°    | 106.7  | 111.5  | 116.0  | 126.4  | 136.7  | 131.7  | 126.6  | 128.8  | 130.6  | 146.0  | 161.4  |
| 67.5°  | 99.3   | 103.5  | 107.5  | 111.0  | 114.4  | 114.9  | 115.5  | 117.6  | 119.7  | 138.0  | 156.1  |
| 70°    | 91.1   | 94.5   | 98.0   | 100.3  | 102.5  | 103.5  | 104.3  | 107.0  | 109.6  | 129.6  | 149.5  |
| 72.5°  | 81.8   | 84.7   | 87.3   | 89.5   | 91.6   | 92.4   | 92.9   | 95.6   | 98.2   | 119.5  | 140.7  |
| 75°    | 71.7   | 74.1   | 76.2   | 78.0   | 79.9   | 81.0   | 82.0   | 83.9   | 85.7   | 108.8  | 131.7  |
| 77.5°  | 60.5   | 62.9   | 65.0   | 66.6   | 68.0   | 69.0   | 69.8   | 72.2   | 74.6   | 94.0   | 113.1  |
| 80°    | 47.3   | 50.2   | 52.8   | 54.2   | 55.2   | 55.5   | 55.5   | 57.6   | 59.7   | 73.5   | 87.1   |
| 82.5°  | 33.4   | 36.6   | 39.6   | 40.6   | 41.7   | 41.7   | 41.7   | 44.1   | 46.5   | 55.7   | 64.8   |
| 85°    | 19.6   | 23.1   | 26.3   | 27.3   | 28.4   | 28.9   | 29.2   | 30.3   | 31.1   | 37.7   | 44.1   |
| 87.5°  | 6.1    | 9.0    | 11.7   | 12.2   | 12.7   | 13.8   | 14.9   | 15.1   | 15.1   | 19.6   | 24.2   |
| 90°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 92.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 95°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 97.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 100°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 102.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 105°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 107.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 110°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |



REPORT NUMBER: P385943  
 CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 275° | 280° | 285° | 290° | 295° | 300° | 305° | 310° | 315° | 320° | 325° |
|--------|------|------|------|------|------|------|------|------|------|------|------|
| 112.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 115°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 117.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 120°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 122.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 125°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 127.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 130°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 132.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 135°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 137.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 140°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 142.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 145°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 147.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 150°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 152.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 155°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 157.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 160°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 162.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 165°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 167.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 170°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 172.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 175°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 177.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 180°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |



REPORT NUMBER: P385943

CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 330°   | 335°   | 340°   | 345°   | 350°   | 355°   | 360°   |
|--------|--------|--------|--------|--------|--------|--------|--------|
| 0°     | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 | 2022.9 |
| 2.5°   | 1990.3 | 2017.3 | 2048.9 | 2080.2 | 2107.1 | 2133.9 | 2156.2 |
| 5°     | 1768.8 | 1823.3 | 1889.9 | 1956.3 | 2015.5 | 2074.7 | 2143.4 |
| 7.5°   | 1490.6 | 1561.0 | 1647.3 | 1733.5 | 1817.2 | 1900.5 | 2006.2 |
| 10°    | 1289.1 | 1360.6 | 1451.9 | 1542.9 | 1636.9 | 1730.6 | 1850.1 |
| 12.5°  | 1161.2 | 1219.1 | 1307.5 | 1395.9 | 1506.3 | 1616.5 | 1731.4 |
| 15°    | 1076.8 | 1139.9 | 1226.0 | 1312.0 | 1432.8 | 1553.6 | 1685.8 |
| 17.5°  | 986.8  | 1069.3 | 1179.5 | 1289.7 | 1432.8 | 1575.6 | 1731.4 |
| 20°    | 892.5  | 995.3  | 1138.1 | 1280.9 | 1473.6 | 1666.1 | 1865.0 |
| 22.5°  | 798.5  | 917.5  | 1100.7 | 1283.6 | 1535.5 | 1787.2 | 2055.6 |
| 25°    | 713.9  | 851.1  | 1077.8 | 1304.3 | 1625.5 | 1946.5 | 2279.4 |
| 27.5°  | 649.6  | 799.3  | 1068.5 | 1337.5 | 1739.6 | 2141.8 | 2522.8 |
| 30°    | 592.5  | 744.9  | 1057.4 | 1369.8 | 1849.6 | 2329.0 | 2713.1 |
| 32.5°  | 543.2  | 691.8  | 1035.9 | 1379.7 | 1926.3 | 2472.9 | 2874.3 |
| 35°    | 504.4  | 650.4  | 999.8  | 1349.1 | 1974.3 | 2599.5 | 3042.1 |
| 37.5°  | 470.9  | 608.7  | 958.6  | 1308.5 | 2017.1 | 2725.6 | 3230.8 |
| 40°    | 439.1  | 564.1  | 923.3  | 1282.2 | 2076.0 | 2869.8 | 3430.2 |
| 42.5°  | 408.8  | 527.5  | 894.9  | 1262.3 | 2130.7 | 2998.8 | 3604.6 |
| 45°    | 386.3  | 499.4  | 869.7  | 1239.8 | 2166.0 | 3092.2 | 3736.0 |
| 47.5°  | 375.1  | 482.6  | 856.2  | 1229.4 | 2201.3 | 3172.9 | 3845.1 |
| 50°    | 373.5  | 479.7  | 871.5  | 1263.4 | 2277.8 | 3291.9 | 3969.9 |
| 52.5°  | 373.3  | 484.5  | 915.9  | 1347.3 | 2419.8 | 3492.0 | 4105.0 |
| 55°    | 367.7  | 487.4  | 968.7  | 1449.8 | 2610.4 | 3770.8 | 4347.9 |
| 57.5°  | 350.7  | 477.3  | 1023.1 | 1568.7 | 2811.9 | 4054.8 | 4621.6 |
| 60°    | 324.4  | 452.9  | 1068.0 | 1682.8 | 2947.3 | 4211.5 | 4727.0 |
| 62.5°  | 291.5  | 410.2  | 1082.9 | 1755.3 | 2943.6 | 4131.8 | 4620.8 |
| 65°    | 263.3  | 365.3  | 1034.0 | 1702.5 | 2794.6 | 3886.5 | 4410.8 |
| 67.5°  | 238.4  | 320.4  | 911.9  | 1503.1 | 2526.8 | 3550.2 | 4143.8 |
| 70°    | 220.3  | 291.0  | 754.5  | 1218.0 | 2191.5 | 3164.7 | 3834.5 |
| 72.5°  | 208.9  | 276.9  | 615.1  | 953.0  | 1778.4 | 2603.5 | 3279.9 |
| 75°    | 193.3  | 254.9  | 482.6  | 710.1  | 1361.1 | 2012.0 | 2477.4 |
| 77.5°  | 164.1  | 214.8  | 363.7  | 512.6  | 998.7  | 1484.5 | 1722.9 |
| 80°    | 126.6  | 165.9  | 250.1  | 334.2  | 687.3  | 1040.4 | 1174.7 |
| 82.5°  | 90.3   | 115.7  | 151.6  | 187.4  | 456.6  | 725.5  | 736.7  |
| 85°    | 55.7   | 67.4   | 86.8   | 106.2  | 302.1  | 498.0  | 414.9  |
| 87.5°  | 30.0   | 35.8   | 45.9   | 55.7   | 96.6   | 137.5  | 79.1   |
| 90°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 92.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 95°    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 97.5°  | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 100°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 102.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 105°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 107.5° | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |
| 110°   | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    | 0.0    |



REPORT NUMBER: P385943  
 CATALOG NUMBER: GAW-SA1C-740-U-SLL

**CANDELA DISTRIBUTION (continued):**

|        | 330° | 335° | 340° | 345° | 350° | 355° | 360° |
|--------|------|------|------|------|------|------|------|
| 112.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 115°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 117.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 120°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 122.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 125°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 127.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 130°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 132.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 135°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 137.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 140°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 142.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 145°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 147.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 150°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 152.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 155°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 157.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 160°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 162.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 165°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 167.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 170°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 172.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 175°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 177.5° | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |
| 180°   | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  | 0.0  |

(END OF REPORT)