

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: STREETWORKS

Report Number: P967230

Luminaire Tested: **NVN-SB4D-740-U-SLR-HSS**

Issue Date: 1/21/2025

Test Information

Test Method: LM-79-08
Report Number: P967230
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2411-289-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/21/2025
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: STREETWORKS
Catalog Number: NVN-SB4D-740-U-SLR-HSS
Description: NAVION ROADWAY AND AREA HIGH DENSITY LED LUMINAIRE
(4) 70 CRI, 4000K, 900mA LIGHTSQUARES WITH 26 LEDS EACH AND SPILL LIGHT
ELIMINATOR RIGHT OPTICS WITH HOUSE SIDE SHIELD
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 33753.3 lumens
Efficiency: N/A
Efficacy: 115.0 lumens/watt
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')
IES Classification: Type IV - Short
BUG Rating: B3 - U0 - G5


Input Watts (W): 293.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



REPORT NUMBER: P967230
 CATALOG NUMBER: NVN-SB4D-740-U-SLR-HSS

Iso-Footcandle Lines of Horizontal Illumination


× Max cd
 - - - 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 10.4 fc
 Type IV - Short - N/A

REPORT NUMBER: P967230
CATALOG NUMBER: NVN-SB4D-740-U-SLR-HSS

Luminous Intensity Polar Plot



REPORT NUMBER: P967230
 CATALOG NUMBER: NVN-SB4D-740-U-SLR-HSS

FLUX DISTRIBUTION:

		Downward	Upward	Total
House Side	Lumens	4726.9	0.0	4726.9
	% Fixture	14.0	0.0	14.0
Street Side	Lumens	29026.4	0.0	29026.4
	% Fixture	86.0	0.0	86.0
Total	Lumens	33753.3	0.0	33753.3
	% Fixture	100.0	0.0	100.0

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	460.1	1.4
10°-20°	1379.4	4.1
20°-30°	2032.1	6.0
30°-40°	2610.7	7.7
40°-50°	4222.3	12.5
50°-60°	7404.2	21.9
60°-70°	9264.7	27.4
70°-80°	5413.8	16.0
80°-90°	965.9	2.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	33753.3	100.0
0°-180°	33753.3	100.0

Coefficient of Utilization



REPORT NUMBER: P967230


CATALOG NUMBER: NVN-SB4D-740-U-SLR-HSS

LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:

Zone	Lumens	% Fixture	Zone Rating/Lumen Limit		
			B	U	G
FL (0°-30°)	2632.6	7.8			
FM (30°-60°)	11830.1	35.0			
FH (60°-80°)	13634.8	40.4			G5
FVH (80°-90°)	928.8	2.8			G5
BL (0°-30°)	1239.0	3.7	B3/2500		
BM (30°-60°)	2407.1	7.1	B2/2500		
BH (60°-80°)	1043.7	3.1	B3/2500		G3/2500
BVH (80°-90°)	37.1	0.1			G1/100
UL (90°-100°)	0.0	0.0		U0/0	
UH (100°-180°)	0.0	0.0		U0/0	

BUG Rating: B3-U0-G5

Type IV Short



REPORT NUMBER: P967230
 CATALOG NUMBER: NVN-SB4D-740-U-SLR-HSS

CANDELA DISTRIBUTION (FULL):

	0°	5°	15°	25°	35°	45°	55°	65°	75°	85°	90°
0°	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8
2.5°	5280.6	5190.0	5136.5	5003.9	4871.4	4764.4	4620.3	4525.0	4411.0	4301.7	4204.0
5°	5885.2	5738.7	5562.0	5320.2	5099.3	4873.7	4655.1	4438.9	4211.0	4001.7	3873.9
7.5°	6396.7	6185.2	5873.6	5552.7	5271.4	4999.2	4743.5	4457.5	4180.8	3853.0	3678.5
10°	6787.3	6517.7	6108.4	5687.5	5364.3	5089.9	4841.2	4599.4	4320.3	3925.0	3706.4
12.5°	7024.5	6736.2	6250.2	5757.3	5387.6	5080.6	4887.7	4780.7	4671.4	4278.5	4022.7
15°	7199.0	6887.4	6350.3	5806.1	5334.1	4957.4	4815.6	4922.6	5048.1	4797.0	4501.7
17.5°	7380.3	7052.5	6480.5	5827.0	5190.0	4718.0	4657.5	4934.1	5224.8	5213.3	4920.2
20°	7552.4	7226.9	6594.4	5813.1	4957.4	4427.3	4480.8	4834.2	5171.3	5313.2	5155.0
22.5°	7750.0	7405.9	6703.7	5759.7	4655.1	4155.2	4322.6	4676.0	4971.4	5138.8	5089.9
25°	7991.8	7631.4	6857.1	5680.5	4329.6	3929.6	4162.2	4492.4	4731.9	4848.1	4845.8
27.5°	8252.3	7901.2	7061.7	5638.7	4066.9	3769.2	3980.8	4273.8	4487.8	4569.1	4569.1
30°	8575.5	8215.1	7303.6	5592.2	3894.8	3676.3	3792.5	4020.4	4229.7	4311.0	4311.0
32.5°	8929.0	8563.9	7536.1	5480.6	3790.1	3606.5	3608.8	3752.9	3943.6	4041.3	4055.2
35°	9370.8	8982.4	7784.9	5236.4	3706.4	3525.1	3429.8	3499.5	3657.6	3773.8	3804.1
37.5°	10000.9	9531.2	8089.5	4887.7	3583.2	3399.5	3241.4	3257.7	3378.6	3506.4	3553.0
40°	10870.5	10268.2	8447.6	4525.0	3406.5	3222.8	3034.4	3027.4	3115.8	3241.4	3292.5
42.5°	12047.1	11242.6	8877.8	4178.5	3236.7	3008.9	2815.9	2804.3	2874.0	2983.3	3036.8
45°	13600.3	12488.9	9405.6	3880.9	3104.2	2799.6	2608.9	2604.3	2662.4	2757.8	2813.5
47.5°	15588.4	14221.2	9933.5	3678.5	3034.4	2634.5	2439.2	2448.5	2499.7	2585.7	2625.2
50°	18162.5	16479.0	10093.9	3576.2	3034.4	2546.1	2288.0	2334.5	2376.4	2441.5	2464.7
52.5°	21248.1	18646.2	9563.8	3483.3	3053.1	2557.8	2160.2	2260.1	2290.4	2346.1	2355.4
55°	24108.2	19708.8	8222.0	3355.3	3057.7	2629.8	2050.8	2199.6	2255.5	2276.4	2274.1
57.5°	25768.4	19343.7	6647.8	3139.1	3039.1	2678.7	1981.1	2125.2	2232.2	2246.2	2225.3
60°	25452.2	18062.6	4894.7	2974.0	2901.9	2660.1	1960.2	2011.4	2181.1	2202.0	2174.1
62.5°	23015.2	15913.9	3397.2	2846.1	2599.6	2578.7	1953.2	1832.3	2069.5	2120.6	2081.1
65°	18499.6	12528.5	2399.6	2450.8	2278.8	2402.0	1916.0	1646.3	1934.6	2004.4	1943.9
67.5°	13421.4	8477.9	1732.4	1985.7	2064.9	2116.0	1832.3	1511.4	1781.1	1874.1	1795.1
70°	8612.7	4578.4	1216.1	1311.5	1739.3	1797.4	1688.2	1390.5	1625.3	1732.4	1646.3
72.5°	6122.3	2704.3	874.3	918.5	1397.5	1497.4	1485.8	1255.6	1444.0	1574.2	1471.9
75°	4224.9	1490.5	590.6	655.7	1013.8	1216.1	1146.4	1078.9	1223.0	1355.7	1255.6
77.5°	2648.5	667.4	353.4	455.7	665.0	955.7	786.0	834.8	953.4	1076.6	971.9
80°	1474.2	258.1	197.6	302.3	362.7	695.3	434.8	537.1	702.2	790.6	706.8
82.5°	320.9	32.6	88.4	130.2	141.9	404.6	230.2	311.6	441.8	434.8	376.7
85°	0.0	0.0	16.3	18.6	9.3	174.4	83.7	102.3	144.1	134.9	102.3
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P967230
 CATALOG NUMBER: NVN-SB4D-740-U-SLR-HSS

CANDELA DISTRIBUTION (continued):

	95°	105°	115°	125°	135°	145°	155°	165°	175°	180°	185°
0°	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8
2.5°	4185.5	4071.5	3987.8	3945.9	3911.1	3943.6	3962.2	3962.2	4041.3	4087.8	4106.4
5°	3792.5	3587.8	3432.1	3327.5	3264.6	3285.5	3308.8	3334.4	3434.4	3501.8	3546.0
7.5°	3520.5	3206.5	2969.3	2822.8	2746.1	2757.8	2774.1	2795.0	2892.7	2960.0	3018.2
10°	3469.3	3018.2	2683.3	2490.3	2397.4	2381.1	2371.7	2364.8	2422.9	2474.0	2520.6
12.5°	3678.5	3027.4	2560.1	2325.2	2211.3	2162.4	2106.7	2062.5	2071.8	2104.3	2162.4
15°	4053.0	3146.0	2520.6	2239.2	2097.4	2016.0	1950.9	1897.4	1885.8	1897.4	1906.7
17.5°	4480.8	3306.5	2516.0	2164.8	1988.1	1904.3	1850.9	1802.1	1785.8	1788.1	1799.7
20°	4764.4	3434.4	2501.9	2081.1	1883.4	1809.0	1762.5	1713.7	1697.4	1702.1	1704.4
22.5°	4792.3	3501.8	2481.0	1988.1	1778.8	1716.1	1669.5	1625.3	1623.0	1623.0	1636.9
25°	4641.2	3501.8	2436.8	1904.3	1678.8	1623.0	1581.2	1527.7	1537.0	1541.6	1560.3
27.5°	4406.4	3418.1	2353.2	1836.9	1592.7	1534.6	1492.8	1444.0	1455.6	1462.6	1483.5
30°	4173.8	3311.2	2253.2	1760.2	1511.4	1444.0	1413.8	1371.9	1376.6	1385.8	1409.1
32.5°	3957.5	3197.2	2134.6	1697.4	1430.0	1362.6	1339.4	1292.8	1299.8	1309.1	1334.7
35°	3743.6	3071.6	1995.1	1623.0	1355.7	1288.2	1269.6	1216.1	1220.8	1234.7	1262.6
37.5°	3513.5	2939.1	1881.1	1548.6	1283.5	1213.8	1195.1	1139.4	1144.0	1160.3	1192.9
40°	3271.6	2808.9	1769.6	1469.5	1206.8	1137.0	1120.7	1060.4	1065.0	1083.5	1118.5
42.5°	3027.4	2667.0	1683.5	1367.2	1127.7	1053.3	1037.1	981.2	988.2	1009.1	1044.1
45°	2801.9	2497.3	1627.7	1253.3	1053.3	969.6	953.4	902.2	916.1	939.4	974.3
47.5°	2608.9	2323.0	1604.4	1157.9	974.3	883.6	869.6	827.8	851.1	876.6	904.6
50°	2443.8	2155.5	1574.2	1060.4	899.8	809.1	795.2	767.3	797.6	823.2	848.7
52.5°	2325.2	1964.8	1509.1	971.9	834.8	746.4	741.8	727.9	755.7	779.0	802.2
55°	2222.9	1767.2	1404.5	895.2	776.6	692.9	697.6	690.6	713.8	732.5	753.4
57.5°	2130.0	1595.1	1271.9	834.8	713.8	646.5	660.4	651.1	662.7	674.3	699.9
60°	2018.3	1420.8	1113.8	767.3	639.4	599.9	616.2	590.6	588.2	593.0	599.9
62.5°	1853.2	1185.9	948.7	683.6	574.3	548.8	555.8	506.9	469.7	469.7	476.6
65°	1623.0	953.4	795.2	590.6	499.9	479.0	474.4	404.6	353.4	348.8	369.7
67.5°	1355.7	783.6	660.4	497.6	416.3	402.3	406.9	355.8	304.6	299.9	323.2
70°	1104.5	648.7	532.5	397.6	320.9	334.9	355.8	304.6	255.7	248.8	269.7
72.5°	897.6	516.2	416.3	304.6	237.2	276.8	302.3	248.8	202.3	197.6	216.3
75°	692.9	379.0	297.7	206.9	172.1	213.9	237.2	181.3	144.1	137.1	153.4
77.5°	462.7	234.8	167.4	130.2	102.3	146.5	158.2	95.3	83.7	81.4	93.0
80°	281.4	109.3	72.1	62.8	34.8	53.5	62.8	39.6	44.2	46.5	55.8
82.5°	141.9	30.2	11.6	2.4	0.0	0.0	18.6	9.3	18.6	23.3	34.8
85°	11.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	4.6	11.6	20.9
87.5°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	9.3
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P967230

CATALOG NUMBER: NVN-SB4D-740-U-SLR-HSS

CANDELA DISTRIBUTION (continued):

	195°	205°	215°	225°	235°	245°	255°	265°	270°	275°	285°
0°	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8
2.5°	4236.6	4334.2	4427.3	4576.1	4729.6	4880.7	5034.2	5183.0	5236.4	5276.0	5364.3
5°	3748.3	3932.0	4145.9	4441.2	4757.4	5083.0	5413.1	5715.5	5852.6	5945.6	6154.9
7.5°	3243.7	3483.3	3790.1	4234.3	4729.6	5248.1	5766.6	6243.3	6464.2	6643.2	6961.8
10°	2743.8	3004.2	3392.5	3899.4	4569.1	5313.2	6029.4	6685.0	6971.1	7196.6	7629.2
12.5°	2304.3	2548.5	2955.4	3515.7	4318.0	5262.0	6180.5	6968.8	7305.9	7559.4	8033.7
15°	1995.1	2167.2	2527.5	3132.1	4020.4	5096.9	6189.8	7103.7	7473.4	7738.4	8150.0
17.5°	1823.0	1881.1	2116.0	2741.5	3690.2	4880.7	6103.8	7150.1	7545.4	7791.9	8077.9
20°	1730.0	1739.3	1804.4	2234.6	3267.0	4678.4	6022.4	7196.6	7612.9	7819.8	7905.8
22.5°	1655.6	1655.6	1671.9	1827.7	2720.6	4436.6	5996.8	7278.0	7705.8	7833.8	7657.1
25°	1588.1	1588.1	1592.7	1634.7	2155.5	4066.9	5980.6	7403.6	7833.8	7868.6	7382.7
27.5°	1518.4	1520.7	1520.7	1544.0	1737.0	3564.6	5910.8	7566.3	7987.2	7915.2	7119.9
30°	1448.6	1453.2	1453.2	1469.5	1537.0	2976.3	5773.6	7761.7	8187.2	7975.6	6859.5
32.5°	1378.8	1383.5	1383.5	1397.5	1446.3	2376.4	5601.5	7940.7	8389.5	8001.2	6617.6
35°	1306.8	1313.7	1309.1	1327.7	1378.8	1890.4	5383.0	8119.7	8608.1	8082.5	6499.0
37.5°	1234.7	1239.3	1237.1	1255.6	1313.7	1632.3	5129.5	8254.6	8905.7	8264.0	6640.9
40°	1162.7	1160.3	1160.3	1181.2	1244.0	1557.9	4810.9	8468.6	9333.5	8582.5	7259.5
42.5°	1088.2	1088.2	1083.5	1106.8	1183.6	1502.1	4506.3	8852.2	9956.7	9089.4	8356.9
45°	1020.8	1018.4	1009.1	1030.1	1125.4	1404.5	4399.4	9568.4	10877.5	9910.2	9684.6
47.5°	955.7	953.4	930.1	948.7	1055.6	1316.1	4799.4	10740.4	12154.0	11117.0	10928.7
50°	897.6	899.8	855.7	872.0	985.9	1248.7	5666.6	12261.0	13849.2	12742.4	12107.6
52.5°	844.1	844.1	786.0	795.2	899.8	1188.2	6492.0	13909.7	16086.0	15009.5	13481.8
55°	790.6	786.0	720.8	725.5	813.8	1102.2	6615.4	15518.7	19136.8	18420.6	15360.5
57.5°	730.1	720.8	660.4	660.4	734.8	1039.4	5734.1	16755.7	22922.3	23433.9	18069.5
60°	655.7	648.7	609.3	597.6	672.0	1095.2	4045.9	16899.9	25363.8	30100.4	23257.1
62.5°	560.4	569.7	548.8	532.5	611.5	1137.0	2397.4	15739.6	24773.2	32221.0	29470.2
65°	441.8	479.0	474.4	462.7	672.0	958.0	1416.0	13512.0	22961.8	30509.5	28202.9
67.5°	376.7	402.3	395.3	395.3	704.6	727.9	890.5	10556.6	20469.1	28479.6	25191.7
70°	320.9	346.4	320.9	320.9	532.5	441.8	616.2	7371.0	17778.8	26233.4	23215.2
72.5°	265.1	290.7	262.7	244.2	425.5	330.2	451.1	4606.3	15225.8	23894.2	21861.9
75°	202.3	232.6	211.6	188.4	281.4	246.5	341.8	2676.4	12614.5	20443.5	19934.3
77.5°	127.9	167.4	158.2	132.5	206.9	179.1	246.5	1592.7	9733.5	15974.4	17146.4
80°	79.0	86.0	88.4	83.7	118.6	121.0	167.4	906.8	6661.8	11133.2	13395.7
82.5°	51.1	51.1	39.6	44.2	58.1	69.8	95.3	341.8	3915.7	6778.1	9324.2
85°	37.2	32.6	20.9	20.9	27.9	34.8	37.2	104.7	1588.1	2676.4	3646.0
87.5°	18.6	16.3	7.0	9.3	13.9	11.6	9.3	4.6	400.0	855.7	599.9
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P967230
 CATALOG NUMBER: NVN-SB4D-740-U-SLR-HSS

CANDELA DISTRIBUTION (continued):

	295°	305°	315°	325°	335°	345°	355°	360°
0°	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8	4673.8
2.5°	5410.9	5482.9	5487.5	5487.5	5424.8	5422.5	5294.5	5280.6
5°	6371.2	6417.7	6429.3	6406.0	6280.5	6187.5	5938.6	5885.2
7.5°	7250.1	7343.1	7343.1	7287.3	7082.7	6892.0	6531.6	6396.7
10°	7952.4	8059.3	8036.1	7922.1	7664.0	7401.2	6964.2	6787.3
12.5°	8294.2	8403.5	8343.0	8212.8	7961.7	7684.9	7224.5	7024.5
15°	8287.2	8257.0	8194.2	8177.9	8057.0	7847.7	7417.5	7199.0
17.5°	7991.8	7736.1	7687.3	7850.1	8003.5	7952.4	7585.0	7380.3
20°	7524.5	7078.0	7033.9	7345.5	7782.6	8005.9	7740.7	7552.4
22.5°	7031.5	6550.3	6447.9	6792.1	7450.1	8022.1	7938.4	7750.0
25°	6564.2	6080.5	5978.2	6299.1	7080.4	7994.2	8152.3	7991.8
27.5°	6173.6	5706.2	5610.8	5931.7	6724.6	7915.2	8366.3	8252.3
30°	5871.2	5438.8	5369.0	5678.3	6417.7	7817.5	8638.3	8575.5
32.5°	5694.5	5378.3	5403.9	5657.3	6252.6	7710.6	8898.7	8929.0
35°	5868.9	5882.9	6106.1	6210.8	6406.0	7694.3	9252.2	9370.8
37.5°	6736.2	7219.9	7682.6	7596.6	7157.1	7882.6	9779.9	10000.9
40°	8212.8	9205.6	9956.7	9628.8	8522.1	8459.2	10540.4	10870.5
42.5°	10017.1	11700.7	12937.7	12058.7	10282.3	9468.4	11626.3	12047.1
45°	11921.6	14776.9	16725.5	14897.9	12158.8	10882.1	13270.2	13600.3
47.5°	13928.2	18515.9	21036.5	18046.3	13898.0	12491.3	15511.7	15588.4
50°	16123.2	22615.4	25431.2	21192.3	15576.8	14335.1	18250.8	18162.5
52.5°	18213.6	26831.0	29732.9	24352.3	17051.1	16623.1	21429.5	21248.1
55°	20208.7	31044.4	34060.2	27389.1	18441.5	19646.0	25205.7	24108.2
57.5°	22522.3	34832.2	38520.0	30439.8	20385.4	23571.0	29428.4	25768.4
60°	25942.7	39136.2	43563.5	34620.6	24082.6	27696.0	30942.1	25452.2
62.5°	30309.6	43093.8	47230.4	38717.6	27796.0	28472.7	28712.1	23015.2
65°	31158.3	44096.0	47437.3	39812.8	27317.0	24152.4	23440.8	18499.6
67.5°	28907.5	42284.6	44544.8	37773.6	24164.0	18664.7	17590.5	13421.4
70°	26382.3	38831.6	39503.6	34306.6	21252.8	13728.2	11879.6	8612.7
72.5°	23794.2	34225.3	32834.8	29793.4	18678.7	9996.2	8568.5	6122.3
75°	20720.3	28168.0	25863.7	24754.6	15465.2	7845.4	6199.1	4224.9
77.5°	16593.0	19827.4	19211.2	19187.9	11621.6	5731.7	4136.6	2648.5
80°	11705.3	12868.0	12554.0	14451.4	7796.6	4157.5	2490.3	1474.2
82.5°	5666.6	7115.2	7303.6	8605.7	3792.5	2446.2	574.3	320.9
85°	2218.3	3432.1	2894.9	3267.0	1065.0	681.3	13.9	0.0
87.5°	248.8	397.6	365.1	288.3	130.2	27.9	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)