

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: STREETWORKS

Report Number: P964680

Luminaire Tested: **NVN-SB3C-827-U-SL2-HSS**

Issue Date: 1/21/2025

**Test Information**

Test Method: LM-79-08  
Report Number: P964680  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2411-289-11)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/21/2025  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: STREETWORKS  
Catalog Number: NVN-SB3C-827-U-SL2-HSS  
Description: NAVION ROADWAY AND AREA HIGH DENSITY LED LUMINAIRE  
(3) 80 CRI, 2700K, 615mA LIGHTSQUARES WITH 26 LEDS EACH AND TYPE II SPILL  
LIGHT ELIMINATOR OPTICS WITH HOUSE SIDE SHIELD  
Light Source: -  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 16232.9 lumens  
Efficiency: N/A  
Efficacy: 108.9 lumens/watt  
Luminous Opening: Rectangular (W 1' x L: 1' x H: 0')  
IES Classification: Type II - Medium  
BUG Rating: B1 - U0 - G3  
  
Input Watts (W): 149.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



REPORT NUMBER: P964680  
 CATALOG NUMBER: NVN-SB3C-827-U-SL2-HSS

### Iso-Footcandle Lines of Horizontal Illumination


✕ Max cd  
 - - - 1/2 Max cd



Based on 25 foot mounting height. Maximum calculated value = 5.9 fc  
 Type II - Medium - N/A

REPORT NUMBER: P964680  
CATALOG NUMBER: NVN-SB3C-827-U-SL2-HSS

### Luminous Intensity Polar Plot



REPORT NUMBER: P964680

CATALOG NUMBER: NVN-SB3C-827-U-SL2-HSS


**FLUX DISTRIBUTION:**

		Downward	Upward	Total
<b>House Side</b>	Lumens	1661.4	0.0	1661.4
	% Fixture	10.2	0.0	10.2
<b>Street Side</b>	Lumens	14571.5	0.0	14571.5
	% Fixture	89.8	0.0	89.8
<b>Total</b>	Lumens	16232.9	0.0	16232.9
	% Fixture	100.0	0.0	100.0

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	255.2	1.6
10°-20°	684.1	4.2
20°-30°	1082.7	6.7
30°-40°	1675.1	10.3
40°-50°	2544.2	15.7
50°-60°	3507.5	21.6
60°-70°	3705.5	22.8
70°-80°	2542.0	15.7
80°-90°	236.6	1.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-90°	16232.9	100.0
0°-180°	16232.9	100.0

**Coefficient of Utilization**



REPORT NUMBER: P964680


CATALOG NUMBER: NVN-SB3C-827-U-SL2-HSS

**LUMINAIRE CLASSIFICATION SYSTEM LUMEN TABLE AND BUG RATING:**

Zone	Lumens	% Fixture	Zone Rating/Lumen Limit		
			B	U	G
FL (0°-30°)	1575.4	9.7			
FM (30°-60°)	6961.9	42.9			
FH (60°-80°)	5804.0	35.8			G3/7500
FVH (80°-90°)	230.2	1.4			G3/500
BL (0°-30°)	446.6	2.8	B1/500		
BM (30°-60°)	764.9	4.7	B1/1000		
BH (60°-80°)	443.5	2.7	B1/500		G1/500
BVH (80°-90°)	6.4	0.0			G0/10
UL (90°-100°)	0.0	0.0		U0/0	
UH (100°-180°)	0.0	0.0		U0/0	

**BUG Rating: B1-U0-G3**

Type II Medium



REPORT NUMBER: P964680

CATALOG NUMBER: NVN-SB3C-827-U-SL2-HSS

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	15°	25°	35°	45°	55°	65°	75°	76°	85°
0°	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2
2.5°	3261.1	3218.0	3226.4	3183.2	3163.3	3114.8	3064.2	2997.9	2924.2	2924.2	2852.6
5°	3604.4	3577.0	3577.0	3526.5	3487.6	3411.7	3321.2	3204.3	3065.3	3051.6	2915.7
7.5°	3815.0	3798.1	3808.7	3779.2	3747.6	3668.7	3561.3	3408.5	3211.6	3194.8	2990.5
10°	3856.0	3855.0	3884.5	3893.0	3914.0	3874.0	3778.2	3602.4	3356.0	3331.7	3054.7
12.5°	3697.1	3677.1	3749.8	3835.0	3955.1	4008.8	3959.3	3779.2	3487.6	3453.8	3114.8
15°	3435.9	3440.1	3509.6	3641.3	3841.4	4033.0	4097.2	3951.9	3621.2	3581.2	3171.7
17.5°	3286.5	3270.6	3330.6	3448.6	3669.7	3940.3	4161.5	4113.0	3763.4	3718.2	3229.6
20°	3268.5	3267.5	3281.1	3334.8	3503.3	3807.7	4154.1	4269.9	3930.9	3878.2	3312.7
22.5°	3392.7	3390.7	3379.1	3368.6	3414.9	3678.1	4122.4	4419.4	4131.0	4074.1	3430.7
25°	3583.4	3580.2	3562.3	3498.0	3452.8	3608.6	4093.0	4558.5	4367.8	4304.7	3573.9
27.5°	3816.1	3813.9	3781.3	3684.5	3567.5	3615.0	4078.3	4701.7	4641.6	4579.5	3739.2
30°	4101.4	4097.2	4029.8	3893.0	3740.2	3715.0	4098.3	4862.7	4927.0	4879.6	3929.7
32.5°	4459.5	4447.9	4359.4	4153.0	3939.3	3848.7	4136.2	5028.0	5265.0	5220.7	4184.7
35°	4736.4	4718.5	4666.9	4484.7	4169.9	4013.0	4224.6	5223.9	5671.4	5632.5	4510.0
37.5°	4974.3	4956.5	4914.4	4764.8	4500.6	4222.5	4366.8	5485.1	6151.6	6132.7	4907.0
40°	5231.3	5201.8	5181.8	5021.8	4782.8	4524.8	4570.1	5790.4	6704.4	6706.6	5384.0
42.5°	5429.2	5417.6	5419.8	5296.6	5055.4	4882.8	4839.5	6134.7	7366.8	7386.8	5957.9
45°	5598.8	5589.3	5628.3	5542.0	5330.3	5117.6	5155.4	6524.4	8091.2	8132.4	6600.2
47.5°	5729.3	5739.9	5795.8	5739.9	5615.7	5282.8	5435.6	6944.6	8852.6	8857.8	7263.6
50°	5859.9	5864.1	5956.8	5929.4	5878.9	5492.5	5693.6	7414.1	9655.0	9664.4	7883.8
52.5°	5901.0	5894.7	6042.1	6109.5	6111.6	5751.5	6027.4	7925.9	10441.6	10472.1	8522.0
55°	5690.4	5708.3	5946.3	6220.1	6328.6	6109.5	6478.1	8573.5	11279.7	11292.3	9153.8
57.5°	4660.6	4759.6	5286.0	5921.0	6468.6	6622.3	7125.7	9330.7	12247.4	12235.8	9794.0
60°	2828.4	2946.3	3576.0	4965.9	6011.6	7137.3	8079.7	10503.7	13304.6	13272.0	10441.6
62.5°	1581.6	1617.4	1818.6	2972.6	4572.1	6809.8	9011.6	12010.5	14724.1	14613.5	11078.6
65°	1165.6	1177.2	1224.7	1456.3	2247.1	5237.6	8807.3	13812.2	16718.5	16521.6	11842.0
67.5°	1013.0	1024.6	1070.9	1102.5	1003.5	2751.5	7256.2	14811.5	19250.9	18992.9	12875.0
70°	852.9	859.3	934.0	955.1	718.1	1046.7	4661.6	14502.9	21594.9	21410.6	13983.9
72.5°	636.0	661.3	769.8	820.3	575.9	556.0	2194.4	12680.2	21991.9	21994.0	13909.0
75°	431.7	454.9	579.1	675.0	444.3	389.6	885.6	9468.5	19149.9	19149.9	12192.7
77.5°	294.8	313.8	403.3	529.6	336.9	267.4	459.1	6009.5	13738.5	14221.8	8690.4
80°	130.6	142.2	260.0	384.4	255.8	172.7	260.0	3290.7	8308.1	8206.0	3406.5
82.5°	64.3	73.7	166.4	240.1	165.3	106.4	136.9	1564.8	2692.5	2558.8	531.8
85°	12.6	16.8	89.5	102.1	76.9	47.4	51.6	481.2	324.3	370.6	112.6
87.5°	0.0	0.0	27.4	19.0	8.4	10.6	10.6	43.2	25.3	29.5	29.5
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

REPORT NUMBER: P964680  
 CATALOG NUMBER: NVN-SB3C-827-U-SL2-HSS

**CANDELA DISTRIBUTION (continued):**

	90°	95°	105°	115°	125°	135°	145°	155°	165°	175°	180°
0°	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2	2805.2
2.5°	2814.6	2775.7	2690.4	2606.2	2519.9	2440.8	2386.1	2331.4	2297.6	2282.9	2285.0
5°	2836.8	2757.8	2578.8	2391.3	2206.0	2024.9	1889.1	1761.7	1721.7	1655.3	1659.6
7.5°	2871.5	2743.1	2460.8	2144.9	1843.8	1578.4	1386.8	1234.1	1173.0	1114.1	1113.0
10°	2894.7	2715.6	2305.0	1882.7	1475.3	1177.2	994.0	883.4	843.5	807.7	806.6
12.5°	2904.1	2665.1	2126.1	1589.0	1147.8	897.2	787.6	736.1	722.3	709.7	709.7
15°	2912.6	2615.7	1926.0	1305.7	906.6	750.8	707.7	690.7	681.3	672.9	672.9
17.5°	2919.9	2552.5	1697.4	1061.4	765.6	691.8	670.8	652.8	645.4	636.0	636.0
20°	2945.2	2491.4	1493.1	876.1	688.7	649.7	626.6	607.6	601.3	594.9	596.0
22.5°	2992.6	2441.9	1295.2	750.8	642.4	606.5	577.1	556.0	551.8	547.6	544.4
25°	3049.5	2380.9	1108.8	669.7	597.1	557.1	524.4	506.5	502.2	503.4	501.2
27.5°	3122.1	2313.4	948.7	618.1	557.1	510.7	473.9	460.1	462.3	466.5	464.3
30°	3202.2	2251.3	823.5	582.3	521.2	469.7	432.8	423.3	430.7	437.0	434.9
32.5°	3321.2	2196.6	736.1	553.9	489.6	435.9	406.4	394.8	403.3	411.7	409.6
35°	3483.4	2169.2	686.5	529.6	462.3	409.6	380.2	371.7	380.2	382.2	381.2
37.5°	3682.3	2167.1	665.5	509.6	437.0	387.6	354.9	351.7	358.0	359.1	357.0
40°	3939.3	2180.8	649.7	494.9	410.7	362.2	331.7	328.5	330.7	338.0	336.9
42.5°	4264.6	2237.6	627.6	475.9	382.2	336.9	312.7	305.3	304.3	312.7	311.7
45°	4673.2	2362.9	598.1	445.5	357.0	315.9	291.7	283.2	280.1	282.2	285.4
47.5°	5118.6	2516.7	568.7	417.0	339.1	299.1	274.8	264.3	259.0	259.0	259.0
50°	5550.4	2690.4	548.6	387.6	326.5	283.2	257.0	246.4	238.0	235.9	234.8
52.5°	5977.9	2861.0	532.8	358.0	311.7	263.2	240.1	228.5	219.0	214.8	212.7
55°	6367.5	3023.1	505.4	329.6	292.7	242.2	223.2	211.7	200.1	192.7	189.5
57.5°	6741.3	3157.9	454.9	300.1	263.2	222.2	205.3	192.7	179.0	169.5	165.3
60°	7081.4	3227.4	391.8	268.5	233.8	201.1	185.3	173.7	155.8	140.0	135.8
62.5°	7340.4	3200.0	323.3	232.7	203.3	182.1	162.2	150.6	129.6	110.6	103.2
65°	7605.8	3050.5	258.0	194.9	177.9	156.9	135.8	124.2	100.0	80.1	74.7
67.5°	7950.1	2731.5	203.3	162.2	153.8	124.2	106.4	99.0	82.1	63.1	58.9
70°	8171.3	2121.8	158.0	131.6	126.4	90.5	82.1	81.1	65.3	48.5	43.2
72.5°	7564.7	1391.0	121.1	100.0	90.5	58.9	63.1	63.1	47.4	32.6	28.4
75°	6314.8	814.0	87.4	71.6	51.6	37.9	43.2	43.2	29.5	15.8	12.6
77.5°	4510.0	433.9	57.9	44.2	26.3	16.8	23.2	22.1	9.4	1.0	0.0
80°	1724.8	149.5	27.4	17.9	7.4	3.2	2.2	1.0	1.0	0.0	0.0
82.5°	263.2	38.9	5.2	4.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85°	47.4	5.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5°	10.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)